

PRODUCT-DETAILS

# 316ERS6W

## Wall mounted outlets, 3P+E, 16A, 380 ... 415 V



### Información General

Extended Product Type	316ERS6W
Product ID	2CMA101221R1000
EAN	7392696012218
Catalog Description	Wall mounted outlets, 3P+E, 16A, 380 ... 415 V
Long Description	Wall mounted outlet, 3P+E, 16A, 380 ... 415 V Clock Position Of Grounding Contact 6 hour Color code Red

### Clasificación

E-Number (Sweden)	E2417616
EAN	7392696012218
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

### Dimensiones

Product Net Width	89 mm
Product Net Height	117 mm
Product Net Length	150 mm
Product Net Depth /	150 mm

Length	
Product Net Weight	0.27 kg

### Información de Embalaje

Package Level 1 Width	134 mm
Package Level 1 Depth / Length	177 mm
Package Level 1 Height	467 mm
Package Level 1 Gross Weight	1.35 kg
Package Level 1 EAN	7392696020107
Package Level 1 Units	box 5 piece

### Technical UL/CSA

Ampere Rating UL/CSA	20 A
Tightening Torque UL/CSA	7.1 in-lb

### Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616293
REACH Declaration	2CMC700005D0001

### Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm <sup>2</sup>
Cable Diameter	25 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316ERS6W
Mounting Holes	40x63.5, 40x73.5
Mounting Type	Angled
Number of Poles	4
Order Multiple	5 piece
Product Main Type	ERS

---

Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current ( $I_n$ )	16 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

---

---

## Clasificaciones

---

eClass	27440510
UNSPSC	39120000

---

---

## Technical

---

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

---

---

## Categorías

---

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

