



Principal

Gama	Mini Pragma
Tipo de producto o componente	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	2
Type of front cover	Translucid
Width	268 mm outside
Height	353 mm outside
Depth	102 mm outside

Complementos

Enclosure mounting	Surface
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	1 trunking flange 1 bare flange
Terminal block function	Without
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Colour	Front face: white (RAL 9003) Door: translucid

Ambiente

Normas	IEC 60439-3 IEC 529 IEC 60670-24 IEC 60695-2-11 EN 50102
Quality labels	IMQ
Fire resistance	Door: 650 °C Front face: 650 °C Back part: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Temperatura ambiente de trabajo	-25...60 °C

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Need no specific recycling operations

Garantia contractual

Warranty period	18 months
-----------------	-----------
