

PRODUCT-DETAILS

332BP6

Ind. P&S#332BP6



Información General

Extended Product Type	332BP6
Product ID	2CMA102223R1000
EAN	7392696022231
Catalog Description	Ind. P&S#332BP6
Long Description	4x32A / IP 44 - Plug Clock Position Of Grounding Contact 6 hour Color code Red

Clasificación

EAN	7392696022231
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensiones

Product Net Width	63 mm
Product Net Height	63 mm
Product Net Length	149 mm
Product Net Depth / Length	149 mm
Product Net Weight	0.205 kg

Información de Embalaje

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.233 kg
Package Level 1 EAN	7392696037006
Package Level 1 Units	box 10 piece

Technical UL/CSA

Ampere Rating UL/CSA	32 A
----------------------	------

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-40 ... 70 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332BP6
Number of Poles	4
Order Multiple	10 piece
Product Main Type	BP
Product Name	Plug
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Voltage (U_r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instructions and Manuals

2CMC700014C0016

RAL Number

RAL 7012 - Gris basalto

Clasificaciones

eClass

27440509

UNSPSC

39120000

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Basic & Safe

