

Hoja de datos del producto 13977

Características

Tablero Mini Keadra 1 fila 6 módulos 200 x 159 x 112mm



Principal

Gama	Keadra
Tipo de producto o componente	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Accessories included with enclosure	1 marking kit

Complementos

Enclosure mounting	Surface
Number of 18 mm modules per row	6
Total number of 18 mm modules	6
Number of horizontal rows	1
Clase de aislamien eléctrico	Clase II Double insulation
Equipo suministrado	1 marking kit
Type of front cover	Transparent
Power dissipation in W	11 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	3
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	159 mm
Height	200 mm
Depth	112 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)

Ambiente

Normas	EN 50102 IEC 60529 EN 50262 IEC 60439-3 IEC 60695-2-1 IEC 670
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	Resistencia UV class 3 conforme a ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Temperatura ambiente de trabajo	-25...60 °C

Garantía contractual

Warranty period	18 months
-----------------	-----------