

Hoja de datos del producto 13978

Características

Tablero Mini Keadra 1 fila 8 módulos 200 x 195 x 112mm



Principal

| | |
|-------------------------------------|-----------------------------------|
| Gama | Kaetra |
| Tipo de producto o componente | Weatherproof enclosure |
| Enclosure type | Mini enclosure for modular device |
| Accessories included with enclosure | 1 marking kit |

Complementos

| | |
|---------------------------------|---|
| Enclosure mounting | Surface |
| Number of 18 mm modules per row | 8 |
| Total number of 18 mm modules | 8 |
| Number of horizontal rows | 1 |
| Clase de aislamien eléctrico | Double insulation Clase II |
| Equipo suministrado | 1 marking kit |
| Type of front cover | Transparent |
| Power dissipation in W | 15 W |
| [In] rated current | 63 A |
| Type of rail | DIN |
| Number of pre-cutouts PG ISO | 5 |
| Locking options description | Optional keylock |
| Enclosure material | Self-extinguishing polymer |
| Width | 195 mm |
| Height | 200 mm |
| Depth | 112 mm |
| Colour | Door : transparent green Enclosure : light grey (RAL 7035) |

Ambiente

| | |
|---------------------------------|---|
| Normas | IEC 670 IEC 60695-2-1 IEC 60439-3 EN 50102 IEC 60529 EN 50262 |
| Fire resistance | 650 °C conforming to IEC 60695-2-1 |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK09 conforming to EN 50102 |
| Environmental characteristic | Resistencia UV class 3 conforme a ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013 |
| Overvoltage category | II |
| Temperatura ambiente de trabajo | -25...60 °C |

Garantía contractual

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|