

Hoja de datos del producto 13983

Características

Tablero Mini Keadra 1 fila 24 modulos 460 x 340 x 160mm



Principal

Gama	Keadra
Tipo de producto o componente	Weatherproof enclosure
Enclosure type	Enclosure for modular device
Accessories included with enclosure	2 wiring straps 2 marking kits 1 terminal block 4 holes 1 terminal block 22 holes 1 terminal block support

Complementos

Enclosure mounting	Surface
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Clase de aislamien eléctrico	Double insulation Clase II
Equipo suministrado	2 marking kit 2 wiring strap 1 terminal block 4 holes 1 terminal block support 1 terminal block 22 holes
Type of front cover	Transparent Reversible
Power dissipation in W	34 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 with 22 outgoers 1 with 4 outgoers
Distribution block outgoers	13 x 10 mm ² 13 x 16 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	460 mm
Depth	160 mm
Colour	Door : transparent green Enclosure : light grey (RAL 7035)

Ambiente

Normas	IEC 60529 EN 50262 IEC 670 EN 50102 IEC 60439-3 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristic	Resistencia UV class 3 conforme a ISO 4582 2010 Ultraviolet degradation test conforming to ISO 4892-2 2013
Overvoltage category	II
Temperatura ambiente de trabajo	-25...60 °C

Garantía contractual

Warranty period	18 months
-----------------	-----------