

PRODUCT-DETAILS

# 316C6W

## Ind. P&S#316C6W



### Información General

Extended Product Type	316C6W
Product ID	2CMA166554R1000
EAN	7392696665544
Catalog Description	Ind. P&S#316C6W
Long Description	Connector, earthing sleeve position 6h, rated current 16A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

### Clasificación

E-Number (Sweden)	E2416369
E-Number (Finland)	2421666
E-Number (Norway)	2416369
EAN	7392696665544
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensiones

Product Net Width	78 mm
Product Net Height	88 mm

Product Net Length	168 mm
Product Net Depth / Length	168 mm
Product Net Weight	0.31 kg

### Información de Embalaje

Package Level 1 Width	95 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	175 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	7392696665544
Package Level 1 Units	box 1 piece
Package Level 2 Units	400 piece

### Technical UL/CSA

Ampere Rating UL/CSA	16 A
Tightening Torque UL/CSA	7.1 in·lb

### Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
REACH Declaration	2CMC700005D0001

### Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm <sup>2</sup>
Cable Diameter	13 ... 17 mm
Cable Entry Position	Cable entry compression gland
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#316C6W

Number of Poles	4
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current ( $I_n$ )	16 A
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700002D0001
RAL Number	RAL 7001 - Gris plata

## Clasificaciones

eClass	27440509
UNSPSC	39120000

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Connectors

