

PRODUCT-DETAILS

# 463P6

## Ind. P&S#463P6



### Información General

Extended Product Type	463P6
Product ID	2CMA166764R1000
EAN	7392696667647
Catalog Description	Ind. P&S#463P6
Long Description	Plug, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

### Clasificación

E-Number (Sweden)	E2416231
E-Number (Finland)	2421626
E-Number (Norway)	1565183
EAN	7392696667647
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

### Dimensiones

Product Net Width	103 mm
Product Net Height	103 mm

Product Net Length	215 mm
Product Net Depth / Length	215 mm
Product Net Weight	0.64 kg

### Información de Embalaje

Package Level 1 Width	114 mm
Package Level 1 Depth / Length	114 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	0.72 kg
Package Level 1 EAN	7392696667647
Package Level 1 Units	box 1 piece
Package Level 2 Units	171 piece

### Technical UL/CSA

Ampere Rating UL/CSA	63 A
Tightening Torque UL/CSA	31 in-lb

### Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

### Información Adicional

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm <sup>2</sup>
Cable Diameter	17 ... 35 mm
Cable Entry Position	Cable entry, membrane
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463P6
Number of Poles	5
Order Multiple	1 piece

Product Main Type	TP
Product Name	Industrial Plug
Protection Type	Splashproof
Rated Current ( $I_n$ )	63 A
Rated Voltage ( $U_r$ )	200/346 ... 240/415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Plugs
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7001 - Gris plata

---

## Clasificaciones

eClass	27440509
UNSPSC	39121402

---

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	3.5 N·m

---

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Plugs

