

PRODUCT-DETAILS

363C6W

Ind. P&S#363C6W



Información General

Extended Product Type	363C6W
Product ID	2CMA166894R1000
EAN	7392696668941
Catalog Description	Ind. P&S#363C6W
Long Description	Connector, earthing sleeve position 6h, rated current 63A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416412
E-Number (Finland)	2421722
E-Number (Norway)	1563873
EAN	7392696668941
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensiones

Product Net Width	108 mm
Product Net Height	112 mm

Product Net Length	286 mm
Product Net Depth / Length	286 mm
Product Net Weight	0.83 kg
Mechanical Drawings	9AKK107492A4188

Información de Embalaje

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	0.83 kg
Package Level 1 EAN	7392696668941
Package Level 1 Units	box 1 piece
Package Level 2 Units	66 piece

Technical UL/CSA

Ampere Rating UL/CSA	63 A
Tightening Torque UL/CSA	31 in-lb

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614200
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	4 ... 16 mm ²
Cable Diameter	17 ... 35 mm
Cable Entry Position	Cable entry, compression gland, internal and external cable clamp
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#363C6W
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Connectors
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	3.5 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Connectors

