

PRODUCT-DETAILS

463BS6W

Ind. P&S#463BS6W



Información General

Extended Product Type	463BS6W
Product ID	2CMA167362R1000
EAN	7392696673624
Catalog Description	Ind. P&S#463BS6W
Long Description	Surface Inlet, earthing sleeve position 6h, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2417270
E-Number (Finland)	2421556
E-Number (Norway)	1542783
EAN	7392696673624
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensiones

Product Net Width	118 mm
Product Net Height	140 mm

Product Net Length	251 mm
Product Net Depth / Length	251 mm
Product Net Weight	0.99 kg
Mechanical Drawings	9AKK107680A0026

Información de Embalaje

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	1.1 kg
Package Level 1 EAN	7392696673624
Package Level 1 Units	box 1 piece
Package Level 2 Units	125 piece

Technical UL/CSA

Ampere Rating UL/CSA	63 A
Tightening Torque UL/CSA	31 in-lb

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Entry Position	Cable entry Ø32mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Surface inlet
Housing Material	Thermoplastic (PBT)

Invoice Description	Ind. P&S#463BS6W
Mounting Holes	176x76
Number of Poles	5
Order Multiple	1 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current (I_n)	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440519
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	3.5 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Surface Inlets

