



### Principal

Gama	Acti 9
Product name	Acti 9 iLL
Tipo de producto o componente	Modular pilot light
Device short name	IIL
[Us] rated supply voltage	110...130 V DC 110...230 V AC 50/60 Hz

### Complementos

Flashing frequency	2 Hz
Señalizaciones en local	1 LED red, service life 100000 h of constant lighting efficiency (consumption 0.3 W)
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside: ProDis
9 mm pitches	2
Altura	82 mm
Anchura	18 mm
Profundidad	69.5 mm
Colour	White (RAL 9003)
Auxiliary connection terminal	Tunnel type terminal 1 cable(s) rigid 0.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) rigid 2.5 mm <sup>2</sup> Tunnel type terminal 1 cable(s) flexible 0.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) flexible with ferrule 2.5 mm <sup>2</sup> Tunnel type terminal 2 cable(s) flexible 2.5 mm <sup>2</sup>
Wire stripping length	9 mm
Tightening torque	1 N.m

### Ambiente

Normas	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % ( 55 °C )
Temperatura ambiente de trabajo	-35...70 °C
Temperatura ambiente de almacenamiento	-40...80 °C

### Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Perfil Medioambiental</a>
Product end of life instructions	Need no specific recycling operations

## Garantia contractual

---

Warranty period	18 months
-----------------	-----------

---