



Principal

Gama	TeSys
Device short name	GVAE
Tipo de producto o componente	Auxiliary contact block
Compatibilidad del producto	GV3P GV2P GV2ME GV2RT GV2L LS1D32 GV2LE GV3L
Pole contact composition	2 NO
Conexiones - terminales	Screw clamp terminals 1 cable 0.75...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.75...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: solid
Cantidad por set	Juego de 10

Complementos

Mounting location	Front side
[Ui] rated insulation voltage	300 V - conforming to UL 508 300 V - conforming to CSA C22.2 No 14 250 V - conforming to IEC 60947-1
[Ue] tensión de funcionamiento nominal	24...240 V AC 24...60 V CC
[Ith] conventional free air thermal current	2.5 A
Protection type	GG fuse <= 10 A GB2CB06 circuit breaker <= 10 A
Mechanical durability	100000 Ciclos
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	120 VA at 110...120 V AC-15 - electrical durability: 100000 cycles 120 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 60 VA at 48 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	15 W at 48 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 9 W at 60 V DC-13 - electrical durability: 100000 cycles
Tightening torque	<= 1.4 N.m - on screw clamp terminals
Altura	10 mm
Anchura	44.5 mm
Profundidad	15 mm
Peso del producto	0.02 kg

Ambiente

Característica medioambiental	Normal environment
-------------------------------	--------------------

Garantia contractual

Warranty period	18 months
-----------------	-----------
