

PRODUCT-DETAILS

HK4-11

HK4-11 Auxiliary Contact



Información General

Extended Product Type	HK4-11
Product ID	1SAM401901R1001
EAN	4013614265846
Catalog Description	HK4-11 Auxiliary Contact
Long Description	HK4-11 Auxiliary contact 1NO/1NC

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85369095

Descargas Populares

Data Sheet, Technical Information	1SBC100173C0201
-----------------------------------	-----------------

Dimensiones

Product Net Width	16 mm
Product Net Height	55 mm
Product Net Depth / Length	35 mm
Product Net Weight	0.017 kg

Technical

Rated Operational Voltage	230 V AC 220 V DC Main Circuit 230 V
Rated Operational Current AC-15 (I_e)	(230 V) 0.5 A (24 V) 2 A
Rated Operational Current DC-13 (I_e)	(24 V) 1 A (48 V) 0.3 A
Rated Insulation Voltage (U_i)	300 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.5 ... 1.5 mm ² Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible 1/2x 0.5 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1 mm ² Rigid 1/2x 0.5 ... 1.5 mm ² Rigid 1/2x 0.75 ... 2.5 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 10 mm
Recommended Screw Driver	Pozidriv 2
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts CO (SPDT)	0
Conventional Free-air Thermal Current (I_{th})	2.5 A
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 508
Product Name	Auxiliary Contact
Suitable For	MS450 MS451 MO450 MS495 MS496 MS497 MO495 MO496
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	Auxiliary Contact

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Auxiliary Circuit 250 V AC/DC
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-14 AWG Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 ... 10.3 in·lb
Contact Rating UL/CSA	C300 R300

Ambiente

Ambient Air Temperature	Funcionamiento -25 ... +70 °C Almacenamiento -50 ... +80 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

BV Certificate	1SAA937000-0201
CCC Certificate	1SAA937002-3803
Declaration of Conformity - CE	1SAD938506-0050 1SAD938505-0051 1SAD938505-0050
DNV Certificate	1SAA937000-0301
GL Certificate	1SAA937000-0404
GOST Certificate	1SAA937000-2703
RoHS Information	1SAD938506-0050 1SAD938505-0051
UL Certificate	UL_E149922

Información de Embalaje

Package Level 1 Width	46 mm
Package Level 1 Depth / Length	50 mm
Package Level 1 Height	106 mm
Package Level 1 Gross Weight	0.017 kg
Package Level 1 Units	10 piece

Clasificaciones

ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	7.0 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4742 >> Electrical contacts
E-Number (Sweden)	3112302

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Guardamotores → Manual Motor Starters Accessories

