

PRODUCT-DETAILS

## 216RAU6

Socket-outlet, panel mounting, 6h, 16A, IP44, unified flange, angled, 2P+E



### Información General

Extended Product Type	216RAU6
Product ID	2CMA193218R1000
EAN	7392696932189
Catalog Description	Socket-outlet, panel mounting, 6h, 16A, IP44, unified flange, angled, 2P+E
Long Description	Panel mounted socket, earthing sleeve position 6h, rated current 16A, IP44 splashproof, unified flange, angled, 2-poles+earth, frequency 50-60 Hz, color code Blue

### Clasificación

E-Number (Sweden)	E2416637
E-Number (Finland)	2421261
E-Number (Norway)	1547402
EAN	7392696932189
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

### Dimensiones

Product Net Width	110 mm
Product Net Height	96 mm

Product Net Length	110 mm
Product Net Depth / Length	110 mm
Product Net Weight	0.24 kg

### Información de Embalaje

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696662185
Package Level 1 Units	box 10 piece
Package Level 2 Units	450 piece

### Technical UL/CSA

Ampere Rating UL/CSA	16 A
Tightening Torque UL/CSA	7.1 in-lb

### Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

### Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	6 ... 13 mm
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P_#216RAU6
Mounting Holes	85x85
Mounting Type	Unified angled flange

Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERAU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	200 ... 250 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC00058M0001
Installation Manual	2CMC00058M0001
RAL Number	RAL 7001 - Gris plata

## Clasificaciones

eClass	27440504
UNSPSC	39121406

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

