

PRODUCT-DETAILS

## CAL16-11B

### CAL16-11B Auxiliary Contact Block



#### Información General

Extended Product Type	CAL16-11B
Product ID	SK829002-B
EAN	7320500050422
Catalog Description	CAL16-11B Auxiliary Contact Block
Long Description	2 pole screw type right side mounted auxilliary contact block, instantaneous N.O. and N.C. contacts, suitable for standard industrial environments

#### Clasificación

EAN	7320500050422
Minimum Order Quantity	1 piece
Customs Tariff Number	85369010

#### Dimensiones

Product Net Width	12.5 mm
Product Net Height	68 mm
Product Net Depth / Length	70 mm
Product Net Weight	0.05 kg

#### Información de Embalaje

Package Level 1 Units	bag 1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	18 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Gross Weight	0.06 kg
Package Level 1 EAN	7320500050422

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Información Adicional

Conventional Free-air Thermal Current ( $I_{th}$ )	acc. to IEC 60947-5-1, $q = 40\text{ °C}$ 16 A
Connecting Terminals (delivered in open position)	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20
Minimum Switching Capacity	0.25 VA/ 12 V / 5 mA
Power Loss	at Rated Operating Conditions per Pole 0.2 W
Product Main Type	CAL16
Product Name	Auxiliary Contact Block
Rated Breaking Capacity acc. to IEC 60947-5-1	10 x $I_e$ AC-15
Rated Frequency (f)	Supply Circuit 50 60 Hz
Rated Insulation Voltage ( $U_i$ )	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Making Capacity acc. to IEC 60947-5-1	10 x $I_e$ AC-15
Rated Operational Current AC-15 ( $I_e$ )	(220 / 240 V) 6 A (24 / 127 V) 6 A (380 / 440 V) 4 A (500 V) 1 A (690 V) 1 A
Rated Operational Current DC-13 ( $I_e$ )	(125 V) 1.8 A (24 V) 6 A (250 V) 0.6 A (48 V) 6 A (72 V) 4 A
Rated Short-time Withstand Current ( $I_{cw}$ )	for 0.1 s 100 A for 1 s 50 A
Replaced Product ID (OLD)	SK829001-B
RoHS Date	1713
Suitable For	A-line
Suitable for Product Class	CONTACTORS
Technical Information	AUXILIARY CONTACT

## Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	1SBC100122C0202
Declaration of Conformity - CE	2CMT2015-005448
Instructions and Manuals	5309660-30

### Clasificaciones

ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
Object Classification Code	K
UNSPSC	39121500
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

### Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Block Contactors Accessories

