



Principal

Gama	Mini Pragma
Tipo de producto o componente	Enclosure
Enclosure type	Modular enclosure
Number of 18 mm modules per row	12
Number of horizontal rows	2
Type of front cover	Plain
Width	270 mm wall 294 mm outside
Height	353 mm wall 377 mm outside
Depth	98 mm total 18 mm outside 80 mm wall

Complementos

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	24
[In] rated current	63 A
Type of rail	35 mm asymmetrical rail
Cable entry	Pre-cutted holes
Terminal block function	Without
Enclosure material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Colour	Door: white (RAL 9003) Front face: white (RAL 9003)

Ambiente

Normas	EN 50102 IEC 529 IEC 60439-3 IEC 60670-24 IEC 60695-2-11
Quality labels	IMQ
Fire resistance	Door: 650 °C Front face: 650 °C Back part: 650 °C
IP degree of protection	IP40
IK degree of protection	IK07
Temperatura ambiente de trabajo	-25...60 °C

La información suministrada en esta documentación contiene descripciones generales y/o características técnicas de los productos incluidos y sus prestaciones. Esta documentación no pretende ser un sustituto de, y no se va a usar para determinar la idoneidad y la fiabilidad de estos productos para aplicaciones específicas de usuario. Es responsabilidad de los usuarios o integradores realizar el análisis de riesgos adecuada y completamente, evaluar y testear los productos en relación con la aplicación específica pertinente o uso del mismo. Ni Schneider Electric Industries SAS ni ninguna de sus filiales o subsidiarias serán responsables por el mal uso de la información contenida en el presente documento.

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Need no specific recycling operations

Garantía contractual

Warranty period	18 months
-----------------	-----------