

PRODUCT-DETAILS

## JB10-10

### JB10-10 Jumper Bar - Orange



#### Información General

|                       |  |
|-----------------------|--|
| Extended Product Type | JB10-10  |
| Product ID            | 1SNK910310R0000  |
| EAN                   | 3472599097766  |
| Catalog Description   | JB10-10 Jumper Bar - Orange  |
| Long Description      | Facilitate & secure your jumper bar assembly process: - Screwless mounting, - Pre-cut poles for alternated jumpering between terminal blocks, - Insulated, - Positive locking, - Perfectly adapted to low level electrical contact (20mA, 50mV). |

#### Clasificación

|                        |          |
|------------------------|----------|
| Color                  | Orange   |
| Minimum Order Quantity | 20 piece |
| Customs Tariff Number  | 85369010 |

#### Descargas Populares

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SNK160031D0201 |
| Instructions and Manuals          | 1SNK160027C0201 |

#### Dimensiones

|                   |       |
|-------------------|-------|
| Product Net Width | 10 mm |
|-------------------|-------|

|                            |         |
|----------------------------|---------|
| Product Net Height         | 98 mm   |
| Product Net Length         | 31.5 mm |
| Product Net Depth / Length | 31.5 mm |
| Product Net Weight         | 24 g    |

## Technical

|   |  |
|---|--|
| Spacing   | 10 mm  |
| Function  | Jumper Bars  |
| Rated Current ( $I_n$ )                         | Main Circuit 76 A  |
| Rated Short-time Withstand Current ( $I_{cw}$ ) | for 1 s 1920 A   |
| Rated Voltage ( $U_r$ )                         | 1000 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )   | 6000 V   |
| Dielectric Test Voltage                         | 2200 V   |
| Pollution Degree                                | 3  |
| Power Loss                                      | 2.4 W  |
| Degree of Protection                            | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Insulation Material                             | Polyamide  |
| Suitable For                                    | ZK10<br>ZK10-3P<br>ZK10-PE<br>ZK10-PE-3P<br>ZS16             |

## Technical UL/CSA

|                                  |                    |
|----------------------------------|--------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| Flammability According to UL94   | V-0                |

## Ambiente

|  |  |
|--|--|
| Ambient Air Temperature                        | Funcionamiento -55 ... +110 °C<br>Almacenamiento -55 ... +110 °C |
| Resistance to Vibrations acc. to IEC 60068-2-6 | Compliant  |
| RoHS Status                                    | Following EU Directive 2002/95/EC August 18, 2005 and amendment  |

## Certificados y Declaraciones (Número de Documento)

|                          |                 |
|--------------------------|-----------------|
| ATEX Certificate         | 1SND162004A1708 |
| CB Certificate           | 1SND161021A0201 |
| Instructions and Manuals | 1SNK160027C0201 |
| RoHS Information         | 1SND230499F0202 |

## Clasificaciones

|                            |   |
|----------------------------|---|
| Object Classification Code | X   |
| ETIM 4                     | EC000489 - Cross-connector for terminal block |
| ETIM 5                     | EC000489 - Cross-connector for terminal block |
| ETIM 6                     | EC000489 - Cross-connector for terminal block |

---

**Información de Embalaje**

---

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 20 piece      |
| Package Level 1 Width          | 50 mm         |
| Package Level 1 Depth / Length | 117 mm        |
| Package Level 1 Height         | 50 mm         |
| Package Level 1 Gross Weight   | 0.48 kg       |
| Package Level 1 EAN            | 3472599097766 |
| Package Level 2 Units          | 600 piece     |
| Package Level 2 Gross Weight   | 14.4 kg       |
| Package Level 3 Units          | 4800 piece    |

---

---

**Categorías**

---

Productos y sistemas de baja tensión → Accesorios de conexión → Terminal Blocks Accessories → Jumper Bars

