



### Principal

Gama	Acti 9
Product name	Acti 9 iCT
Tipo de producto o componente	Contactador
Device short name	ICT
Aplicación de dispositivo	Motor-heating-lighting
Poles description	1P
Pole contact composition	1 NO
Tipo de red	AC
Utilisation category	AC-1 conforming to EN 60947-4-1 AC-3 conforming to EN 60947-4-1 AC-7A conforming to EN 61095 AC-7A conforming to IEC 1095 AC-7B conforming to EN 61095 AC-7B conforming to IEC 1095
Control type	Remote control
[Uc] control circuit voltage	230...240 V AC 50 Hz

### Complementos

[Ie] intensidad de funcionamiento nominal	25 A AC-7A 8.5 A AC-7B
Frecuencia de red	50/60 Hz
[Ue] tensión de funcionamiento nominal	250 V AC 50 Hz
Maximum power	1.2 W 250 V AC
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	4 kV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Señalizaciones en local	Action indicator
Hold-in power consumption in VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Altura	81 mm
Anchura	18 mm
Profundidad	60 mm
Colour	White
Durabilidad eléctrica	200000 Ciclos AC 50/60 Hz conforme a EN 61095 200000 Ciclos AC 50/60 Hz conforme a IEC 1095
Conexiones - terminales	Control circuit: 2 tunnel type terminals 1.5 mm <sup>2</sup> for rigid cable(s) Power circuit: 1 tunnel type terminals 1...4 mm <sup>2</sup> for flexible cable(s) Power circuit: 1 tunnel type terminals 1.5...6 mm <sup>2</sup> for rigid cable(s) Control circuit: 1 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for rigid cable(s) Control circuit : 2 tunnel type terminals 1.5...2.5 mm <sup>2</sup> for flexible cable(s)

Tightening torque	Control circuit: 0.8 N.m Power circuit: 0.8 N.m
Compatibilidad del producto	IACTs IATEt IACTp IACTc

## Ambiente

Normas	EN 61095 IEC 1095
Noise level	30 dB
Heat dissipation	0.9 W at 50/60 Hz
IP degree of protection	IP20
Pollution degree	2
Tropicalisation	2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Temperatura ambiente de trabajo	-5...60 °C
Temperatura ambiente de almacenamiento	-40...70 °C

## Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Perfil Medioambiental</a>
Product end of life instructions	Need no specific recycling operations

## Garantía contractual

Warranty period	18 months
-----------------	-----------