



Principal

Gama	Acti 9
Product name	Acti 9 iCT
Tipo de producto o componente	Contactador
Device short name	ICT
Aplicación de dispositivo	Motor-heating-lighting
Poles description	2P
Pole contact composition	2 NO
Tipo de red	AC
Utilisation category	AC-1 conforming to EN 60947-4-1 AC-3 conforming to EN 60947-4-1 AC-7A conforming to IEC 1095 AC-7A conforming to IEC 1095 AC-7B conforming to EN 61095 AC-7B conforming to IEC 1095
Control type	Remote control
[Uc] control circuit voltage	230...240 V AC 50 Hz

Complementos

[Ie] intensidad de funcionamiento nominal	25 A AC-7A 8.5 A AC-7B
Frecuencia de red	50 Hz
[Ue] tensión de funcionamiento nominal	250 V AC 50 Hz
Maximum power	1.2 W 250 V AC
[Ui] rated insulation voltage	500 V AC 50 Hz
[Uimp] rated impulse withstand voltage	2.5 kV
Control signal type	Maintained
Switching frequency	100 switching operations/day
Señalizaciones en local	Action indicator
Hold-in power consumption in VA	2.7 VA
Inrush power in VA	9.2 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	2
Altura	81 mm
Anchura	18 mm
Profundidad	68 mm
Colour	White
Durabilidad eléctrica	200000 Ciclos AC 50 Hz conforme a EN 61095 200000 Ciclos AC 50 Hz conforme a IEC 1095
Conexiones - terminales	Control circuit: 2 tunnel type terminals 1.5 mm ² for rigid cable(s) Power circuit: 1 tunnel type terminals 1...4 mm ² for flexible cable(s) Power circuit: 1 tunnel type terminals 1.5...6 mm ² for rigid cable(s) Control circuit: 1 tunnel type terminals 1.5...2.5 mm ² for rigid cable(s) Control circuit : 2 tunnel type terminals 1.5...2.5 mm ² for flexible cable(s)

Tightening torque	Control circuit: 0.8 N.m Power circuit: 0.8 N.m
Compatibilidad del producto	IACts IACt 24 IACtp IACtEt IACtc

Ambiente

Normas	EN 61095 IEC 1095
Noise level	30 dB
Heat dissipation	0.9 W at 50/60 Hz
IP degree of protection	IP40 (in modular enclosure) conforming to IEC 60529 IP20 conforming to IEC 60529
Pollution degree	2
Tropicalisation	2 2 conforming to IEC 60068-1
Relative humidity	95 % (55 °C)
Operating altitude	2000 m
Temperatura ambiente de trabajo	-5...60 °C
Temperatura ambiente de almacenamiento	-40...70 °C

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Need no specific recycling operations

Garantía contractual

Warranty period	18 months
-----------------	-----------