



Principal

| | |
|-------------------------------|--|
| Gama de producto | Harmony XALD |
| Tipo de producto o componente | Empty control station |
| Device short name | XALD |
| Destino del producto | For XB5 Ø 22 mm control and signalling units |
| Number of cut-out | 3 cut-outs |
| Colour of base of enclosure | Light grey RAL 7035 |
| Colour of cover | Dark grey RAL 7016 |
| Material | Polycarbonate |
| Cable entry | 2 knock-outs for cable entry, clamping capacity: ≤ 14 mm 2 knock-outs for Pg 13 cable gland and ISO M20, clamping capacity: ≤ 12 mm |
| IP degree of protection | IP69 IP67 IP66 conforming to IEC 60529 IP69K |

Complementos

| | |
|------------------------------------|--|
| Assembly style | For customer assembly |
| Number of horizontal rows | 1 |
| Number of vertical rows | 3 |
| Peso del producto | 0.238 kg |
| Resistance to high pressure washer | 7000000 Pa at 55 °C, distance: 0.1 m |
| Mounting of block | Front mounting Rear mounting |
| Electrical composition code | MF1 SF2 MF2 PF2 SF1 PR1 SR1 PF1 SR2 MR1 |
| Main group | 3 cut-outs |
| Group of product | Standard grey |

Ambiente

| | |
|--|---|
| Protective treatment | TH |
| Temperatura ambiente de almacenamiento | -40...70 °C |
| Temperatura ambiente de trabajo | -40...70 °C |
| Overtoltage category | Class II conforming to IEC 60536 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| IK degree of protection | IK03 conforming to EN 50102 |
| Normas | EN/IEC 60947-5-1 UL 508 JIS C 4520 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 |

Garantia contractual

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|
