

Hoja de datos del producto

Características

XB4BVG4

Luz piloto 22 mm metalico rasante rojo con lente claro 110...120V AC



Principal

Gama de producto	Harmony XB4
Tipo de producto o componente	Complete pilot light
Device short name	XB4
Bezel material	Chromium plated metal
Fixing collar material	Zamak
Mounting diameter	22 mm
Se vende en cantidades indivisibles	1
Shape of signaling unit head	Round
Cap/operator or lens colour	Red
Operator additional information	With plain lens
Light source	Protected LED
Bulb base	Integral LED
Color de la fuente de luz	Rojo
[Us] rated supply voltage	110...120 V AC, 50/60 Hz

Complementos

Altura	47 mm
Anchura	30 mm
Profundidad	54 mm
Terminals description ISO n°1	(X1-X2)PL
Peso del producto	0.08 kg
Resistance to high pressure washer	7000000 Pa at 55 °C, distance: 0.1 m
Conexiones - terminales	Screw clamp terminals: $\leq 2 \times 1.5 \text{ mm}^2$ with cable end conforming to EN/IEC 60947-1 Screw clamp terminals: $1 \times 0.22...2 \times 2.5 \text{ mm}^2$ without cable end conforming to EN/IEC 60947-1
[Ui] rated insulation voltage	250 V (degree of pollution: 3) conforming to EN 60947-1
[Uimp] rated impulse withstand voltage	4 kV conforming to EN 60947-1
Tipo señalización	Steady
Supply voltage limits	100...132 V AC
Consumo de corriente	14 mA
Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV conforming to IEC 61000-4-5

Ambiente

Protective treatment	TH
Temperatura ambiente de almacenamiento	-40...70 °C
Temperatura ambiente de trabajo	-40...70 °C
Electrical shock protection class	Class I conforming to IEC 60536
IP degree of protection	IP69 IP67 IP66 conforming to IEC 60529 IP69K
NEMA degree of protection	NEMA 13 NEMA 4X

IK degree of protection	IK06 conforming to IEC 50102
Normas	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
Certificaciones de producto	CSA UL listed
Vibration resistance	5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 18 ms) para half sine wave acceleration conforme a IEC 60068-2-27 50 gn (duration = 11 ms) para half sine wave acceleration conforme a IEC 60068-2-27
Resistance to fast transients	2 kV conforming to IEC 61000-4-4
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
Electromagnetic emission	Class B conforming to IEC 55011

Garantía contractual

Warranty period	18 months
-----------------	-----------