

### Main

|                                 |                          |
|---------------------------------|--------------------------|
| Range of product                | Harmony XB4              |
| Product or component type       | Complete pilot light     |
| Device short name               | XB4                      |
| Bezel material                  | Chromium plated metal    |
| Fixing collar material          | Zamak                    |
| Mounting diameter               | 22 mm                    |
| Head type                       | Standard                 |
| Sale per indivisible quantity   | 1                        |
| Shape of signaling unit head    | Round                    |
| Cap/Operator or lens colour     | Blue                     |
| Operator additional information | With plain lens          |
| Light source                    | Protected LED            |
| Bulb base                       | Integral LED             |
| Light source colour             | Blue                     |
| [Us] rated supply voltage       | 230...240 V AC, 50/60 Hz |

### Complementary

|  |  |
|--|--|
| Height                                 | 47 mm  |
| Width                                  | 30 mm  |
| Depth                                  | 54 mm  |
| Terminals description ISO n°1          | (X1-X2)PL  |
| Product weight                         | 0.08 kg  |
| Resistance to high pressure washer     | 7000000 Pa at 55 °C, distance: 0.1 m   |
| Connections - terminals                | Screw clamp terminals : $\leq 2 \times 1.5 \text{ mm}^2$ with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals : $1 \times 0.22...2 \times 2.5 \text{ mm}^2$ without cable end conforming to EN/IEC 60947-1 |
| [Ui] rated insulation voltage          | 250 V (degree of pollution: 3) conforming to EN 60947-1  |
| [Uimp] rated impulse withstand voltage | 4 kV conforming to EN 60947-1  |
| Signalling type                        | Steady   |
| Supply voltage limits                  | 195...264 V AC   |
| Current consumption                    | 14 mA  |
| Service life                           | 100000 h at rated voltage and 25 °C  |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                 |                                  |
|-----------------|----------------------------------|
| Surge withstand | 1 kV conforming to IEC 61000-4-5 |
|-----------------|----------------------------------|


## Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TH   |
| Ambient air temperature for storage   | -40...70 °C  |
| Ambient air temperature for operation | -40...70 °C  |
| Electrical shock protection class     | Class I conforming to IEC 60536  |
| IP degree of protection               | IP69<br>IP67<br>IP66 conforming to IEC 60529<br>IP69K  |
| NEMA degree of protection             | NEMA 13<br>NEMA 4X   |
| IK degree of protection               | IK06 conforming to IEC 50102   |
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-5<br>JIS C 4520<br>UL 508<br>CSA C22.2 No 14  |
| Product certifications                | CSA<br>UL listed   |
| Vibration resistance                  | 5 gn (f = 12...500 Hz) conforming to IEC 60068-2-6   |
| Shock resistance                      | 30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27<br>50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27 |
| Resistance to fast transients         | 2 kV conforming to IEC 61000-4-4   |
| Resistance to electromagnetic fields  | 10 V/m conforming to IEC 61000-4-3   |
| Resistance to electrostatic discharge | 6 kV on contact (on metal parts) conforming to IEC 61000-4-2<br>8 kV in free air (in insulating parts) conforming to IEC 61000-4-2   |
| Electromagnetic emission              | Class B conforming to IEC 55011  |

## Contractual warranty

|                 |                     |
|-----------------|---------------------|
| Warranty period | 18 months 18 months |
|-----------------|---------------------|

Dimensions



- e : clamping thickness: 1 to 6 mm / 0.04 to 0.24 in.
- b : 30 mm / 1.18 in.
- c : 46.5 mm / 1.83 in.

Panel Cut-out for Pushbuttons, Switches and Pilot Lights (Finished Holes, Ready for Installation)

| Connection by Screw Clamp Terminals or Plug-in Connectors or on Printed Circuit Board   | Connection by Faston Connectors   |
|---|---|
|    |  |
| <p>(1) Diameter on finished panel or support<br/>           (2) 40 mm min. / 1.57 in. min.<br/>           (3) 30 mm min. / 1.18 in. min.<br/>           (4) <math>\text{Ø } 22.5 \text{ mm} / 0.89 \text{ in. recommended } (\text{Ø } 22.3 \text{ mm }_0^{+0.4} / 0.88 \text{ in. }_0^{+0.016})</math><br/>           (5) 45 mm min. / 1.78 in. min.<br/>           (6) 32 mm min. / 1.26 in. min.</p> |   |