Product data sheet Characteristics

ZBVG6

blue light block for head Ø22 integral LED 110...120V screw clamp terminals



IVIAIII		
Range of product	Harmony XB4 Harmony XB5	
Product or component type	Light block	
Device short name	ZBV	
Sale per indivisible quantity	5	
Connections - terminals	Screw clamp terminals : <= 2 x 1.5 mm² with cable end conforming to EN 60947-1 Screw clamp terminals : >= 1 x 0.22 mm² without cable end conforming to EN 60947-1	
Signalling type	Steady	
Light source	Protected LED	
Bulb base	Integral LED	
Light block supply	Direct	
Light source colour	Blue	
[Us] rated supply voltage	110120 V AC, 50/60 Hz	
	· · · · · · · · · · · · · · · · · · ·	

Complementary

Complementary		- 1
Product weight	0.017 kg	,
Tightening torque	0.81.2 N.m conforming to EN 60947-1	
Shape of screw head	Cross head compatible with Philips no 1 screwdriver Cross head compatible with pozidriv No 1 screwdriver Slotted head compatible with flat Ø 4 mm screwdriver Slotted head compatible with flat Ø 5.5 mm screwdriver	
Current consumption	14 mA	- 4
Service life	100000 h at rated voltage and 25 °C	- J
Surge withstand	1 kV conforming to IEC 61000-4-5	
Mounting of block	Front mounting	7
Electrical composition code	M1 M2 M3 M4 M5 M6 M10 MF1 P1 P2 PE1	

Compatibility code	ZBV	
Environment		
Protective treatment	TH	

Protective treatment	TH
Ambient air temperature for storage	-4070 °C
Ambient air temperature for operation	-4070 °C
IP degree of protection	IP20 conforming to IEC 60529
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508 CSA C22.2 No 14
Product certifications	CSA UL listed
Resistance to fast transients	2 kV conforming to IEC 61000-4-4
Resistance to electromagnetic fields	10 V/m conforming to IEC 61000-4-3
Resistance to electrostatic discharge	6 kV on contact (on metal parts) conforming to IEC 61000-4-2 8 kV in free air (in insulating parts) conforming to IEC 61000-4-2
Electromagnetic emission	Class B conforming to IEC 55011

Contractual warranty

Warranty period	18 months