



Principal

Gama	Acti 9
Product name	Acti 9 iTL
Tipo de producto o componente	Impulse relay
Device short name	ITL
Aplicación de dispositivo	Standard
Poles description	2P
Pole contact composition	2 NO
[In] rated current	16 A
Tipo de red	AC
[Uc] control circuit voltage	110 V DC 230...240 V AC 50/60 Hz

Complementos

Frecuencia de red	50/60 Hz
[Ue] tensión de funcionamiento nominal	250 V AC 50/60 Hz
Control type	Coil deconnection Remote and manual control
Control signal type	Impulse
Switching frequency	5 switching operations/minute 100 switching operations/day
Impulse duration	50 ms...1 s
Remote control type	Illuminated push-button 3 mA
Señalizaciones en local	ON/OFF indication
Mounting mode	Fixed
Mounting support	DIN rail
9 mm pitches	2
Altura	84 mm
Anchura	18 mm
Profundidad	60 mm
Durabilidad eléctrica	AC-22: 100000 cycles AC-21: 200000 cycles
Conexiones - terminales	Control circuit : tunnel type terminals 1 cable(s) 0.5...4 mm ² rigid Control circuit : tunnel type terminals 1 cable(s) 0.5...4 mm ² rigid with cable end Control circuit : tunnel type terminals 1 cable(s) 1...4 mm ² flexible Control circuit : tunnel type terminals 1 cable(s) 1...4 mm ² flexible with ferrule Power circuit : tunnel type terminals 1 cable(s) 1.5...4 mm ² rigid Power circuit : tunnel type terminals 1 cable(s) 1.5...4 mm ² rigid with cable end Power circuit : tunnel type terminals 1 cable(s) 1.5...4 mm ² flexible Power circuit : tunnel type terminals 1 cable(s) 1.5...4 mm ² flexible with ferrule
Wire stripping length	11 mm
Tightening torque	1 N.m
Compatibilidad de la gama	Acti 9 iATeT Acti 9 iATL4 Acti 9 iATLc Acti 9 iATLc+s Acti 9 iATLm Acti 9 iATLs Acti 9 iATLz Acti 9 iETL iTL 16

Ambiente

Normas	EN 669-1 EN 669-2-2
Certificaciones de producto	GOST CCC
Quality labels	NF IMQ KEMA VDE CEBEC
Noise level	60 dB
IP degree of protection	IP20 on opening conforming to IEC 60529 IP40 in enclosure conforming to IEC 60529
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % (55 °C)
Temperatura ambiente de trabajo	-20...50 °C
Temperatura ambiente de almacenamiento	-40...70 °C

Oferta sustentable

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1001 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Perfil Medioambiental
Product end of life instructions	Need no specific recycling operations

Garantía contractual

Warranty period	18 months
-----------------	-----------