

PRODUCT-DETAILS

# CR-U3S

## CR-U3S Socket for 3c/o CR-U relay



### Información General

Extended Product Type	CR-U3S
Product ID	1SVR405660R0000
EAN	4013614528996
Catalog Description	CR-U3S Socket for 3c/o CR-U relay
Long Description	The CR-U3S socket is from the CR-U (universal) relay range. The socket is suitable for CR-U relays with 3 c/o (SPDT) output contacts. The socket has screw connection terminals. Pluggable function modules, holder and marker are available as accessories

### Clasificación

Minimum Order Quantity	10 piece
Customs Tariff Number	85369010

### Descargas Populares

Data Sheet, Technical Information	2CDC117006D0203
Instructions and Manuals	1SVC405650M9000

### Dimensiones

Product Net Width	38 mm
Product Net Height	26 mm

Product Net Depth / Length	75 mm
Product Net Weight	0.065 kg

## Technical

Function	Accessory for interface relays CR-U
Sub-Function	Socket for universal relays
Sub-Function 2	Socket for universal relay 3 c/o
Output	none
Output Signal	none
Terminal Type	Screw Terminals

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificados y Declaraciones (Número de Documento)

CSA Certificate	CSA_262671-2785566
cURus Certificate	cURus508_E244328
Declaration of Conformity - CE	1SVD982020-0001
EAC Certificate	EAC_RU_C-DE.ME77.B.00446-19
Environmental Information	1SAA981009-2401
Instructions and Manuals	1SVC405650M9000
RoHS Information	1SVD982020-0001

## Información de Embalaje

Package Level 1 Units	10 piece
Package Level 1 Width	133 mm
Package Level 1 Height	84 mm
Package Level 1 Depth / Length	81 mm
Package Level 1 Gross Weight	0.652 kg
Package Level 1 EAN	4013614374364

## Clasificaciones

Object Classification Code	K
ETIM 4	EC001456 - Relay socket
ETIM 5	EC001456 - Relay socket
ETIM 6	EC001456 - Relay socket
ETIM 7	EC001456 - Relay socket
eClass	7.0 27371603
UNSPSC	39121516
E-Number (Sweden)	4005436

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos de control → Relés electrónicos → Relés de interface

