



### Principal

|                               |                     |
|-------------------------------|---------------------|
| Gama                          | Acti 9              |
| Product name                  | Acti 9 iSW          |
| Tipo de producto o componente | Switch disconnecter |
| Device short name             | iSW                 |
| Aplicación de dispositivo     | Control             |
| Poles description             | 1P                  |
| Utilisation category          | AC-22A              |
| Suitability for isolation     | Yes                 |

### Complementos

|                                           |                                                                                                                 |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| [Ie] intensidad de funcionamiento nominal | 20 A 250 V AC 50/60 Hz                                                                                          |
| [Ue] tensión de funcionamiento nominal    | 250 V AC 50/60 Hz                                                                                               |
| [Ui] rated insulation voltage             | 250 V AC 50/60 Hz conforming to EN/IEC 60669-2-4                                                                |
| [Uimp] rated impulse withstand voltage    | 4 kV                                                                                                            |
| Control type                              | Toggle                                                                                                          |
| Señalizaciones en local                   | ON/OFF indication                                                                                               |
| Contact position indicator                | Yes                                                                                                             |
| Mounting mode                             | Fixed                                                                                                           |
| Mounting support                          | DIN rail                                                                                                        |
| 9 mm pitches                              | 2                                                                                                               |
| Altura                                    | 77 mm                                                                                                           |
| Anchura                                   | 18 mm                                                                                                           |
| Profundidad                               | 75.5 mm                                                                                                         |
| Colour                                    | Grey                                                                                                            |
| Mechanical durability                     | 300000 Ciclos                                                                                                   |
| Durabilidad eléctrica                     | 30000 Ciclos                                                                                                    |
| Conexiones - terminales                   | Tunnel type terminals: rigid<br>Tunnel type terminals: flexible<br>Tunnel type terminals: flexible with ferrule |
| Longitud de pelado de cable               | 9 mm                                                                                                            |
| Tightening torque                         | 1.2 N.m                                                                                                         |

### Ambiente

|                                        |                  |
|----------------------------------------|------------------|
| Normas                                 | EN/IEC 60669-2-4 |
| IP degree of protection                | IP4              |
| Pollution degree                       | 2                |
| Tropicalisation                        | 2                |
| Relative humidity                      | 95 % at 55 °C    |
| Temperatura ambiente de trabajo        | -20...50 °C      |
| Temperatura ambiente de almacenamiento | -40...70 °C      |

## Oferta sustentable

|                                  |                                                                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                                                              |
| RoHS (date code: YYWW)           | Compliant - since 1001 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a> |
| REACH                            | Reference not containing SVHC above the threshold                                                                                  |
| Product environmental profile    | Available <a href="#">Perfil Medioambiental</a>                                                                                    |
| Product end of life instructions | Available <a href="#">Manual De Gestión Residuos</a>                                                                               |

## Garantía contractual

|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|