

PRODUCT-DETAILS

T7D 1600 3p F F

T7D 1600 3p F F



Información General

| | |
|-----------------------|---|
| Extended Product Type | T7D 1600 3p F F |
| Product ID | 1SDA062040R1 |
| EAN | 8015644645786 |
| Catalog Description | T7D 1600 3p F F |
| Long Description | SWITCH-DISCONNECTOR TMAX T7D 1600 FIXED THREE-POLE WITH FRONT TERMINALS AND LEVER OPERATING MECHANISM |

Clasificación

| | |
|------------------------|---------------|
| EAN | 8015644645786 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

Dimensiones

| | |
|----------------------------|--------|
| Product Net Width | 210 mm |
| Product Net Height | 268 mm |
| Product Net Depth / Length | 154 mm |
| Product Net Weight | 9.7 kg |

Información de Embalaje

| | |
|--------------------------------|---------------|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 280 mm |
| Package Level 1 Height | 350 mm |
| Package Level 1 Depth / Length | 360 mm |
| Package Level 1 Gross Weight | 11.2 kg |
| Package Level 1 EAN | 8015644645786 |

Información Adicional

| | |
|---|---|
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 77 W |
| Product Main Type | SACE Tmax T |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | SD |
| Rated Operational Voltage | 690 V AC 750 V DC |
| Rated Short-time Withstand Current (I _{cw}) | for 1 s 20 A |
| Rated Uninterrupted Current (I _u) | 1600 A |
| Standards | IEC 60947 |
| Sub-type | T7 |
| Suitable For | T7 |
| Suitable for Product Class | Moulded Case Circuit Breakers |
| Terminal Connection Type | Fixed Circuit-Breakers Front |
| Version | F |

Certificados y Declaraciones (Número de Documento)

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SDC210015D0201 |
| Declaration of Conformity - CE | 1SDL000165R0007 |
| Environmental Information | 1SDC210015D0201 |
| Instructions and Manuals | 1SDC210015D0201 |
| RoHS Information | 1SDL000201R0001 |

Clasificaciones

| | |
|----------------------------|---|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000216 - Switch disconnecter |
| ETIM 7 | EC000216 - Switch disconnecter |
| Object Classification Code | Q |
| UNSPSC | 39121100 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax T

