

T7S 1000 PR231 / Entrada PI = 1000A 3p FFM

Información general

Tipo de producto extendido:	T7S 1000 PR231 / Entrada PI = 1000A 3p FFM
ID del Producto:	1SDA062753R1
EAN:	8015644653026
Descripción del catálogo:	T7S 1000 PR231 / Entrada PI = 1000A 3p FFM
Descripción larga:	C. INTERRUPTOR TMAX T7S 1000 FIJO DE TRES POLOS CON TERMINALES FRONTALES Y MECANISMO DE FUNCIONAMIENTO DE ENERGÍA ALMACENADA Y LIBERACIÓN DE ESTADO SÓLIDO EN AC PR231 / PI R 1000

Categorías

Productos »Productos y sistemas de baja tensión» Disyuntores »Disyuntores de caja moldeada» Tmax T

Ordenando

EAN:	8015644653026
Cantidad mínima de pedido:	1 pieza
Número de arancel aduanero:	85362090

Dimensiones

Ancho neto del producto:	210 mm
Product Net Height:	268 mm
Product Net Depth / Length:	178 mm
Product Net Weight:	11 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	280 mm
Package Level 1 Height:	350 mm
Package Level 1 Depth / Length:	360 mm
Package Level 1 Gross Weight:	12.5 kg
Package Level 1 EAN:	8015644653026

Additional Information

Electrical Durability:	2000 cycle 60 cycles per hour
Mechanical Durability:	10000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	at Rated Operating Conditions per Pole 30 W
Product Main Type:	SACE Tmax T
Product Name:	Moulded Case Circuit Breaker
Product Type:	CB
Rated Current (I_n):	Main Circuit 1000 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	1000 V
Rated Operational Voltage:	690 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
---	--

Rated Short-time Withstand Current (I_{cw}):	for 1 s 20 kA
--	---------------

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 50 kA (400 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 40 kA (690 V AC) 30 kA
--	--

Rated Uninterrupted Current (I_u):	1000 A
--	--------

Release:	PR231/P-I
-----------------	-----------

Release Type:	EL
----------------------	----

Short-Circuit Performance Level:	S
---	---

Standards:	IEC
-------------------	-----

Sub-type:	T7
------------------	----

Suitable For:	T7M
----------------------	-----

Suitable for Product Class:	Moulded Case Circuit Breakers
------------------------------------	-------------------------------

Terminal Connection Type:	Fixed Circuit-Breakers Front
----------------------------------	---------------------------------

Version:	F
-----------------	---

Certificates and Declarations (Document Number)

Data Sheet, Technical Information:	1SDC210015D0201
---	---------------------------------

Declaration of Conformity - CE:	1SDL000165R0007
--	---------------------------------

Environmental Information:	1SDC210015D0201
-----------------------------------	---------------------------------

GL Certificate:	1SDL000163R0055
------------------------	---------------------------------

Instructions and Manuals:	1SDC210015D0201
----------------------------------	---------------------------------

RoHS Information:	1SDL000201R0001
--------------------------	---------------------------------

Classifications

ETIM 4:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
----------------	---

ETIM 5:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
----------------	---

ETIM 6:	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
----------------	---

ETIM 7:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
----------------	--

Object Classification Code:	Q
------------------------------------	---

UNSPSC:	39120000
----------------	----------

WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
-----------------------	--



© Copyright 2021 ABB