



Main

| | |
|----------------------------|---------------------------------|
| Range | Miluz |
| Product or component type | Switch and socket-outlet |
| Device presentation | Complete mechanism |
| Outlet poles configuration | 2P + E |
| Outlet standard | Italian |
| Colour tint | Graphite (RAL 7016) Graphite |
| Type of packing | Flow-pack |

Complementary

| | |
|--------------------------------|---|
| Switch function | 1-way |
| [In] rated current | 10 A wiring device |
| [Ue] rated operational voltage | 250 V AC |
| Local signalling | Without |
| Material | Thermoplastic ABS-UV stabilised: cover frame ASA + PC: centre plate PC (polycarbonate): casing Thermoplastic ABS-UV stabilised: rocker PA66: casing PS (polystyrene): fixing frame |
| Number of modules | 2 modules |
| Fixing mode | By screw |
| Connections - terminals | Screw-clamp terminals |
| Cable outer diameter | 4.0 Mm 2.5 Mm |
| AWG gauge | AWG 12 AWG 14 |
| Height | 115.0 Mm |
| Width | 77.0 Mm |
| Depth | 40.0 Mm |
| Embedding depth | 26.0 Mm |
| Projecting depth | 14.5 Mm |

Environment

| | |
|------------------------|--|
| Standards | ABNT NBR NM 60669-2-1 NMX J-508 ANCE NCh 2027/1 NCh 2027/2 IEC 60669 |
| Product certifications | SEC |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 76.4 G |
| Package 1 Height | 4.0 Cm |
| Package 1 width | 9.5 Cm |
| Package 1 Length | 19.0 Cm |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 20 |
| Package 2 Weight | 1.527 Kg |
| Package 2 Height | 21.5 Cm |
| Package 2 width | 15.8 Cm |
| Package 2 Length | 26.5 Cm |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Product Life Status : **Commercialised**