Product data sheet Characteristics

S3B70225

Italian socket outlet, Miluz, 2P+E, 10A, 250V, 1 module, brown



Main

Range	Miluz
Product or component type	Socket-outlet
Fixing mode	Clip-in

Complementary

Device presentation	Mechanism
Outlet standard description	With earthing contact
Outlet poles configuration	2P + E
Device mounting	Flush
Colour tint	Brown (RAL 8014)
Outlet standard	Italian
Type of packing	Flow-pack
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC
Material	ASA + PC: centre plate PC (polycarbonate): casing
Surface finish	Glossy
Number of modules	1 module
Connections - terminals	Screw-clamp terminals
Number of cables	2
Cable cross section	1.52.5 Mm²
Wire stripping length	11 Mm
AWG gauge	AWG 14
Height	22.0 Mm
Width	30.5 Mm
Depth	44.0 Mm
Embedding depth	22.0 Mm
Projecting depth	8.5 Mm

Environment

Standards	NCh 2027/1 NCh 2027/2	
IP degree of protection	IP2x	

Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	17.0 G
Package 1 Height	2.2 Cm
Package 1 width	8.5 Cm
Package 1 Length	14.0 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	50
Package 2 Weight	850.0 G
Package 2 Height	21.5 Cm
Package 2 width	15.8 Cm
Package 2 Length	26.5 Cm

Offer Sustainability

☑ REACh Declaration	
Yes	
Compliant EPEU RoHS Declaration	
Yes	
₫Yes	
☑ China RoHS Declaration	
	Yes Compliant EEU RoHS Declaration Yes Yes

Product Life Status : Commercialised