

E4.2N 4000 Ekip Dip LSIG 3p F HR

Información general

Tipo de producto E4.2N 4000 Ekip Dip LSIG 3p F HR
extendido:

Identificación de producto: 1SDA071193R1

EAN: 8015644750435

Descripción del catálogo: E4.2N 4000 Ekip Dip LSIG 3p F HR

Descripción larga: C. INTERRUPTOR SACE EMAX2 E4.2N 4000 FIJO DE TRES POLOS CON TERMINALES TRASERO HORIZONTAL Y ESTADO SÓLIDO LIBERACIÓN EN AC EKIP / DIP-LSIG R 4000 EQUIPADO CON: 4 CONTACTOS AUXILIARES Y C. INTERRUPTOR EN POSICIÓN ABIERTO-CERRADO

Categorías

Productos »Productos y sistemas de baja tensión» Disyuntores »Disyuntores de potencia» Emax 2

Ordenando

EAN: 8015644750435

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85362090

Dimensions

Product Net Width: 384 mm

Product Net Height: 371 mm

Product Net Depth / Length: 270 mm

Product Net Weight: 56 kg

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 515 mm

Package Level 1 Height: 610 mm

Package Level 1 Depth / Length: 615 mm

Package Level 1 Gross Weight: 63 kg

Package Level 1 EAN: 8015644750435

Environmental

RoHS Status: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Additional Information

Current Type: AC

Electrical Durability:	Ue =< 440 V 5000 cycle Ue = 500 ... 690 V 4000 cycle 20 cycles per hour
Mechanical Durability:	15000 cycle 60 cycles per hour
Number of Poles:	3
Power Loss:	465 W
Product Main Type:	SACE Emax 2
Product Name:	Air Circuit Breaker
Product Type:	Air Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I_{cu} (I_{cs}):	100 %
Rated Current (I_n):	4000 A
Rated Voltage (U_r):	690 V
Rated Impulse Withstand Voltage (U_{imp}):	acc. to IEC 60947-2 12 kV
Rated Insulation Voltage (U_i):	AC 1000 V
Rated Operational Voltage:	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V AC) 66 kA (230 V AC) 66 kA (380 V AC) 66 kA (400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (660 V AC) 66 kA (690 V AC) 66 kA
Rated Short-time Withstand Current (I_{cw}):	for 1 s 66 kA for 3 s 50 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(400 V AC) 66 kA (415 V AC) 66 kA (440 V AC) 66 kA (500 V AC) 66 kA (525 V AC) 66 kA (690 V AC) 66 kA
Rated Uninterrupted Current (I_u):	4000 A
Release:	Ekip Dip LSIG
Release Type:	EL
Short-Circuit Performance Level:	N
Standards:	IEC
Sub-type:	E4.2

Terminal Connection Type: Rear flat Horizontal

Version: F

Certificates and Declarations (Document Number)

Data Sheet, Technical Information: 1SDC200023D0209

Declaration of Conformity - CE: 9AKK106713A5545

Environmental Information: Not Available

Instructions and Manuals: 1SDH001000R0002

Classifications

ETIM 4: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 5: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 6: EC000228 - Power circuit-breaker for trafo/generator/installation prot.

ETIM 7: EC000228 - Power circuit-breaker for trafo/generator/installation protection

Object Classification Code: Q

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)



© Copyright 2021 ABB