



Main

Range	Miluz
Product or component type	Dimmer
Fixing mode	Clip-in

Complementary

Device mounting	Flush
Device presentation	Mechanism
Switch function	Dimmer
Dimmer control	Rotary
Colour tint	Brown (RAL 8014)
Type of packing	Gift box
Dimmer application	Light
Load type	Halogen lamp Halogen lamp Incandescent lamp Incandescent lamp Low voltage halogen lamp with ferromagnetic transformer Low voltage halogen lamp with ferromagnetic transformer LED lamp LED lamp
[Ue] rated operational voltage	127...220 V AC
Power range	150 W 250 W 150 W 250 W 150 W 250 W 50 W 100 W
Material	ABS (acrylonitrile butadiene-styrene): front plate ABS (acrylonitrile butadiene-styrene): knob PC: casing
Network frequency	50...60 Hz
Surface finish	Glossy
Number of modules	1 module
Connections - terminals	Screw terminal block
Cable cross section	0.5...4 Mm ²
Cable stiffness	Rigid Flexible Stranded
Wire stripping length	9 Mm
AWG gauge	AWG 12

Height	22 Mm
Width	44 Mm
Depth	55 Mm
Embedding depth	33 Mm
Net weight	0.024 Kg
Projecting depth	22 Mm

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	37.0 G
Package 1 Height	13.0 Cm
Package 1 width	9.0 Cm
Package 1 Length	5.6 Cm
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Weight	296.0 G
Package 2 Height	10.5 Cm
Package 2 width	13.1 Cm
Package 2 Length	15.8 Cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Product Life Status : **Commercialised**