

## PRODUCT-DETAILS

# XT4N 160 Ekip LS/I In=160A 3p F F

## XT4N 160 Ekip LS/I In=160A 3p F F



### Información General

|                       |                                                                                                               |
|-----------------------|---------------------------------------------------------------------------------------------------------------|
| Extended Product Type | XT4N 160 Ekip LS/I In=160A 3p F F                                                                             |
| Product ID            | 1SDA068125R1                                                                                                  |
| EAN                   | 8015644695958                                                                                                 |
| Catalog Description   | XT4N 160 Ekip LS/I In=160A 3p F F                                                                             |
| Long Description      | C.BREAKER TMAX XT4N 250 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 160 A |

### Clasificación

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644695958 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

### Dimensiones

|                            |          |
|----------------------------|----------|
| Product Net Width          | 105 mm   |
| Product Net Height         | 160 mm   |
| Product Net Depth / Length | 82.5 mm  |
| Product Net Weight         | 2.333 kg |

### Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 145 mm        |
| Package Level 1 Height         | 210 mm        |
| Package Level 1 Depth / Length | 168 mm        |
| Package Level 1 Gross Weight   | 2.456 kg      |
| Package Level 1 EAN            | 8015644695958 |

## Información Adicional

|                                                             |                                                                                                                                                                                  |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circuit Breaker Type to be Associated                       | Power Distribution                                                                                                                                                               |
| Current Type                                                | AC                                                                                                                                                                               |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle                                                                                                                                                |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle                                                                                                                 |
| Number of Poles                                             | 3                                                                                                                                                                                |
| Opening Time                                                | CB with SOR 15 ms<br>CB with UVR 15 ms                                                                                                                                           |
| Order Multiple                                              | 1 piece                                                                                                                                                                          |
| Product Main Type                                           | SACE Tmax XT                                                                                                                                                                     |
| Product Name                                                | Moulded Case Circuit Breaker                                                                                                                                                     |
| Product Type                                                | CB                                                                                                                                                                               |
| Rated Current ( $I_n$ )                                     | 160 A                                                                                                                                                                            |
| Rated Frequency (f)                                         | 50 / 60 Hz                                                                                                                                                                       |
| Rated Voltage ( $U_r$ )                                     | 690 V                                                                                                                                                                            |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV                                                                                                                                                                             |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V                                                                                                                                                                           |
| Rated Operational Voltage                                   | 690 V AC                                                                                                                                                                         |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 65 kA<br>(230 V AC) 65 kA<br>(240 V AC) 65 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 36 kA<br>(500 V AC) 30 kA<br>(525 V AC) 20 kA<br>(690 V AC) 10 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 65 kA<br>(230 V AC) 65 kA<br>(240 V AC) 65 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 36 kA<br>(500 V AC) 30 kA<br>(525 V AC) 20 kA<br>(690 V AC) 10 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 160 A                                                                                                                                                                            |
| Release Type                                                | EL                                                                                                                                                                               |
| Standards                                                   | IEC                                                                                                                                                                              |
| Sub-type                                                    | XT4                                                                                                                                                                              |
| Terminal Connection Type                                    | Fixed Circuit-Breakers                                                                                                                                                           |
| Version                                                     | F                                                                                                                                                                                |

| Certificados y Declaraciones (Número de Documento) |                                    |
|----------------------------------------------------|------------------------------------|
| Data Sheet, Technical Information                  | 1SDC210100D0204<br>1SDC210099D0204 |
| Declaration of Conformity - CE                     | 9AKK106713A5529                    |
| Environmental Information                          | 1SDL000190R0001                    |
| GL Certificate                                     | 1SDL000163R0095                    |
| Instructions and Manuals                           | 1SDH000722R0001                    |
| LR Certificate                                     | 1SDL000163R0100                    |

| Clasificaciones            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q                                                                            |
| UNSPSC                     | 39120000                                                                     |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

### Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT

