

PRODUCT-DETAILS

# OTM400E3CM230C

## OTM400E3CM230C MOTORIZED C/O SWITCH



### Información General

Extended Product Type	OTM400E3CM230C
Product ID	1SCA022847R1630
EAN	6417019297842
Catalog Description	OTM400E3CM230C MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

### Descargas Populares

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303002M0204

### Dimensiones

Product Net Width	323 mm
Product Net Height	185 mm
Product Net Depth / Length	235 mm
Product Net Weight	11 kg

---

**Technical**


---

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	$q = 40 \text{ }^\circ\text{C}$ 400 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 15 kiloampere rms
Motor Operational Voltage	220 ... 240 V AC
Power Loss	10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20

---

**Ambiente**


---

Environmental Information	1SCC303036D0202
---------------------------	-----------------

---



---

**Certificados y Declaraciones (Número de Documento)**


---

Declaration of Conformity - CE	1SCC303013D0202
Environmental Information	1SCC303036D0202
Instructions and Manuals	1SCC303002M0204
RoHS Information	1SCC303036D0202

## Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	255 mm
Package Level 1 Depth / Length	460 mm
Package Level 1 Height	243 mm
Package Level 1 Gross Weight	10.22 kg
Package Level 1 EAN	6417019297842

## Clasificaciones

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122217
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Motorized Change-over Switches

