

Hoja de datos del producto

Características

9001SKR9RH6

Set paro de emergencia base metalica 41mm rojo - NC



Principal

| | |
|---------------------------------|-------------------------------|
| Gama de producto | Harmony 9001SK |
| Tipo de producto o componente | Mushroom head push-button |
| Device short name | 9001SK |
| Type of operator | Push-pull |
| Operator profile | Red mushroom Ø 41 mm unmarked |
| Operator additional information | Screw-on plastic mushroom |

Complementos

| | |
|--|--|
| Bezel material | Plastic |
| Mounting diameter | 30 mm |
| CAD overall width | 46 mm |
| CAD overall height | 45 mm |
| CAD overall depth | 69 mm |
| Peso del producto | 0.159 kg |
| Operating position | Any position |
| Shape of signaling unit head | Round |
| Operator position information | 2 positions |
| Contacts type and composition | 1 NC |
| Positive opening | With conforming to IEC 60947-5-2 |
| Mechanical durability | 5000000 Ciclos |
| Conexiones - terminales | Screw clamp terminals (1 x 0.22...2 x 1.5 mm ²) conforming to EN/IEC 60947-1 |
| Tightening torque | 0.8 N.m conforming to EN/IEC 60947-1 |
| Shape of screw head | Cross slotted head |
| Contacts material | Silver alloy contacts |
| Short-circuit protection | 10 A cartridge fuse conforming to EN/IEC 60947-5-1 |
| [I _{th}] conventional free air thermal current | 10 A |
| [U _i] rated insulation voltage | 250 V (degree of pollution: 3) conforming to EN/IEC 60947-1 |
| [U _{imp}] rated impulse withstand voltage | 2.5 kV conforming to EN/IEC 60947-1 |
| [I _e] intensidad de funcionamiento nominal | 3 A at 240 V AC-15, A600-Q600 conforming to NEMA 0.55 A at 125 V DC-13, A600-Q600 conforming to NEMA |
| [I _{cm}] rated short-circuit making capacity | <= 0.1 kA at 600 V DC-13 <= 12 kA at 600 V AC-15, 7200 VA <= 15 kA at 480 V AC-15, 7200 VA <= 30 kA at 240 V AC-15, 7200 VA <= 60 kA at 120 V AC-15, 7200 VA <= 0.27 kA at 250 V DC-13 <= 0.55 kA at 125 V DC-13 |
| Rated breaking capacity | <= 3 kA at 120 V AC-15, 720 VA <= 6 kA at 600 V AC-15, 720 VA <= 0.1 kA at 125 V DC-13 <= 0.27 kA at 600 V DC-13 <= 0.55 kA at 250 V DC-13 <= 1.2 kA at 480 V AC-15, 720 VA <= 1.5 kA at 240 V AC-15, 720 VA |

La información suministrada en esta documentación contiene descripciones generales y/o características técnicas de los productos incluidos y sus prestaciones. Esta documentación no pretende ser un sustituto de, y no se va a usar para determinar la idoneidad y la fiabilidad de estos productos para aplicaciones específicas de usuario. Es responsabilidad de los usuarios o integradores realizar el análisis de riesgos adecuada y completamente, evaluar y testear los productos en relación con la aplicación específica pertinente o uso del mismo. Ni Schneider Electric Industries SAS ni ninguna de sus filiales o subsidiarias serán responsables por el mal uso de la información contenida en el presente documento.

| | |
|------------------------------|------------------|
| Compatibility code | 9001SK |
| Presentación del dispositivo | Complete product |

Ambiente

| | |
|--|--|
| Protective treatment | TC |
| Temperatura ambiente de almacenamiento | -40...70 °C |
| Temperatura ambiente de trabajo | -25...70 °C |
| Overvoltage category | Class II conforming to IEC 61140 |
| IP degree of protection | IP66 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 4X |
| Normas | CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 |
| Certificaciones de producto | UL 508 NEMA |
| Vibration resistance | 7 gn (f = 2...500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn conforming to IEC 60068-2-27 |

Oferta sustentable

| | |
|------------------------|--|
| RoHS (date code: YYWW) | Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

Garantía contractual

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|