


PRODUCT-DETAILS

216BP6

Ind. P&S#216BP6



Información General

Extended Product Type	216BP6
Product ID	2CMA102145R1000
EAN	7392696021456
Catalog Description	Ind. P&S#216BP6
Long Description	3x16A / IP 44 - Plug Clock Position Of Grounding Contact 6 hour Color code Blue

Clasificación

EAN	7392696021456
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensiones

Product Net Width	47 mm
Product Net Height	47 mm
Product Net Length	124 mm
Product Net Depth / Length	124 mm
Product Net Weight	0.148 kg

Información de Embalaje

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.663 kg
Package Level 1 EAN	7392696036269
Package Level 1 Units	box 10 piece

Technical UL/CSA

Ampere Rating UL/CSA	16 A
----------------------	------

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	2P+E
Ambient Temperature	-40 ... 70 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Entry Position	Anti-kink sleeve
Color	Blue
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216BP6
Number of Poles	3
Order Multiple	10 piece
Product Main Type	BP
Product Name	Plug
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200 ... 250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440501
UNSPSC	39120000

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Basic & Safe

