

## PRODUCT-DETAILS

# 216RAU6W

## Ind. P&S#216RAU6W



### Información General

|                       |                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------|
| Extended Product Type | 216RAU6W                                                                                    |
| Product ID            | 2CMA166996R1000                                                                             |
| EAN                   | 7392696005692                                                                               |
| Catalog Description   | Ind. P&S#216RAU6W                                                                           |
| Long Description      | IEC Receptacle 16A 2P3W 220-240V Clock Position Of Grounding Contact 6 hour Color code Blue |

### Clasificación

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2416695            |
| E-Number (Finland)     | 2421291             |
| E-Number (Norway)      | 1561902             |
| EAN                    | 7392696005692       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensiones

|                    |        |
|--------------------|--------|
| Product Net Width  | 95 mm  |
| Product Net Height | 102 mm |

|                            |         |
|----------------------------|---------|
| Product Net Length         | 95 mm   |
| Product Net Depth / Length | 102 mm  |
| Product Net Weight         | 0.23 kg |

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 110 mm        |
| Package Level 1 Depth / Length | 110 mm        |
| Package Level 1 Height         | 110 mm        |
| Package Level 1 Gross Weight   | 0.23 kg       |
| Package Level 1 EAN            | 7392696005692 |
| Package Level 1 Units          | box 1 piece   |
| Package Level 2 Units          | 420 piece     |

## Technical UL/CSA

|                          |           |
|--------------------------|-----------|
| Ampere Rating UL/CSA     | 16 A      |
| Tightening Torque UL/CSA | 7.1 in·lb |

## Certificados y Declaraciones (Número de Documento)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0022 |
| Declaration                    | 2CMC700005D0022 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0020 |
| SEMKO Certificate              | 1613211         |
| REACH Declaration              | 2CMC700005D0022 |

## Información Adicional

|                        |                     |
|------------------------|---------------------|
| Additional Information | 2P+E                |
| Ambient Temperature    | -25 ... 40 °C       |
| Cable Cross-Section    | 1.5 ... 4 mm²       |
| Cable Diameter         | 6 ... 13 mm         |
| Color                  | Blue                |
| Connection Type        | Screw               |
| Degree of Protection   | IP67<br>IP69        |
| Frequency (f)          | 50 Hz<br>60 Hz      |
| Function               | Receptacle          |
| Housing Material       | Thermoplastic (PBT) |
| Invoice Description    | Ind. P&S#216RAU6W   |
| Mounting Holes         | 79.5x79.5           |

|                            |                                        |
|----------------------------|----------------------------------------|
| Mounting Type              | unified flange, angled                 |
| Number of Poles            | 3                                      |
| Order Multiple             | 1 piece                                |
| Product Main Type          | TRAU                                   |
| Product Name               | Panel mounted socket                   |
| Protection Type            | Watertight                             |
| Rated Current ( $I_n$ )    | 16 A                                   |
| Rated Frequency (f)        | 50...60 Hz                             |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                          |
| Recommended Screw Driver   | PH2                                    |
| RoHS Date                  | L23                                    |
| Standards                  | UL 1682, 1686 / CSA C22.2 No. 182.1-13 |
| Suitable For               | Socket Outlets for Panel Mounting      |
| Suitable for Product Class | IEC Industrial Plugs and Sockets       |
| Instructions and Manuals   | 2CMC700052M0001                        |
| Installation Manual        | 2CMC700052M0001                        |
| RAL Number                 | RAL 7001 - Gris plata                  |

## Clasificaciones

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

## Technical

|                   |               |
|-------------------|---------------|
| Wire Size         | 14 ... 12 AWG |
| Tightening Torque | 0.8 N·m       |

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Socket Outlets for Panel Mounting

