

PRODUCT-DETAILS

316RAU6W

Ind. P&S#316RAU6W



Información General

Extended Product Type	316RAU6W
Product ID	2CMA167012R1000
EAN	7392696670128
Catalog Description	Ind. P&S#316RAU6W
Long Description	Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 16A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416703
E-Number (Finland)	2421270
E-Number (Norway)	1561913
EAN	7392696670128
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensiones

Product Net Width	95 mm
Product Net Height	102 mm

Product Net Length	95 mm
Product Net Depth / Length	102 mm
Product Net Weight	0.15 kg

Información de Embalaje

Package Level 1 Width	110 mm
Package Level 1 Depth / Length	110 mm
Package Level 1 Height	110 mm
Package Level 1 Gross Weight	0.15 kg
Package Level 1 EAN	7392696670128
Package Level 1 Units	box 1 piece
Package Level 2 Units	420 piece

Technical UL/CSA

Ampere Rating UL/CSA	16 A
Tightening Torque UL/CSA	7.1 in·lb

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Cable Diameter	13 ... 17 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet, panel mounting, unified flange, angled
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#316RAU6W
Mounting Holes	79.5x79.5

Mounting Type	unified flange, angled
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRAU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700002D0001
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

Categorias

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Socket Outlets for Panel Mounting

