


PRODUCT-DETAILS

463RS6

Surface socket-outlet, 6h, 63A, IP44, 3P+N+E



Información General

Extended Product Type	463RS6
Product ID	2CMA167484R1000
EAN	7392696674843
Catalog Description	Surface socket-outlet, 6h, 63A, IP44, 3P+N+E
Long Description	Surface socket-outlet, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416518
E-Number (Finland)	2421226
E-Number (Norway)	2416518
EAN	7392696674843
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensiones

Product Net Width	107 mm
Product Net Height	254 mm

Product Net Length	136 mm
Product Net Depth / Length	254 mm
Product Net Weight	1.05 kg
Mechanical Drawings	9AKK107680A0707

Información de Embalaje

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	1.06 kg
Package Level 1 EAN	7392696674843
Package Level 1 Units	box 1 piece
Package Level 2 Units	125 piece

Technical UL/CSA

Ampere Rating UL/CSA	60 A
Tightening Torque UL/CSA	31 in·lb

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614199
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Cable Entry Position	Cable entry, M32, alternative rear knock-out cable entry
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#463RS6
Mounting Holes	170x95

Number of Poles	5
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	63 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	3.5 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

