


## PRODUCT-DETAILS

# 463BS6

## Surface inlet, 6h, 63A, IP44, 3P+N+E



### Información General

|                       |                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 463BS6                                                                                                                                     |
| Product ID            | 2CMA167566R1000                                                                                                                            |
| EAN                   | 7392696675666                                                                                                                              |
| Catalog Description   | Surface inlet, 6h, 63A, IP44, 3P+N+E                                                                                                       |
| Long Description      | Surface Inlet, earthing sleeve position 6h, rated current 63A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

### Clasificación

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417207            |
| E-Number (Finland)     | 2421526             |
| E-Number (Norway)      | 2417207             |
| EAN                    | 7392696675666       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

### Dimensiones

|                    |        |
|--------------------|--------|
| Product Net Width  | 107 mm |
| Product Net Height | 117 mm |

|                            |         |
|----------------------------|---------|
| Product Net Length         | 237 mm  |
| Product Net Depth / Length | 237 mm  |
| Product Net Weight         | 0.85 kg |

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 152 mm        |
| Package Level 1 Depth / Length | 120 mm        |
| Package Level 1 Height         | 265 mm        |
| Package Level 1 Gross Weight   | 0.94 kg       |
| Package Level 1 EAN            | 7392696675666 |
| Package Level 1 Units          | box 1 piece   |
| Package Level 2 Units          | 125 piece     |

## Technical UL/CSA

|                          |          |
|--------------------------|----------|
| Ampere Rating UL/CSA     | 63 A     |
| Tightening Torque UL/CSA | 31 in·lb |

## Certificados y Declaraciones (Número de Documento)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Declaration                    | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1519130         |
| REACH Declaration              | 2CMC700005D0001 |

## Información Adicional

|                        |                                                        |
|------------------------|--------------------------------------------------------|
| Additional Information | 3P+N+E                                                 |
| Ambient Temperature    | -25 ... 40 °C                                          |
| Cable Cross-Section    | 6 ... 25 mm²                                           |
| Cable Entry Position   | Cable entry,M32 alternative rear knock-out cable entry |
| Color                  | Red                                                    |
| Connection Type        | Screw                                                  |
| Degree of Protection   | IP44                                                   |
| Design                 | Surface mounted plug                                   |
| Frequency (f)          | 50 Hz<br>60 Hz                                         |
| Function               | Surface inlet                                          |
| Housing Material       | Plastic (PA)                                           |
| Invoice Description    | Ind. P&S#463BS6                                        |
| Mounting Holes         | 170x95                                                 |

|                            |                                  |
|----------------------------|----------------------------------|
| Number of Poles            | 5                                |
| Order Multiple             | 1 piece                          |
| Product Main Type          | TBS                              |
| Product Name               | Wall mounted inlet               |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 63 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 200/346 ... 240/415 V            |
| Recommended Screw Driver   | PH2                              |
| RoHS Date                  | L23                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable For               | Surface Inlets                   |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC000040M0001                  |
| Installation Manual        | 2CMC000040M0001                  |
| RAL Number                 | RAL 7012 - Gris basalto          |

---

## Clasificaciones

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39121406 |

---

## Technical

|                   |             |
|-------------------|-------------|
| Wire Size         | 8 ... 4 AWG |
| Tightening Torque | 3.5 N·m     |

---

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Inlets

