

GVSUPS10KB4HS

Galaxy VS UPS 10kW 400V, 1 internal 9Ah smart modular battery string, expandable to 4, Start-up 5x8



Overview

Presentation	Highly efficient, easy-to-deploy 10kW, 400V 3-phase UPS that brings-best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 1 smart high-capacity modular battery string, expandable to 4 strings for extended runtime. Run-time charts available in the Documents tab.
Lead time	Usually Ships within 2 Weeks

Main

Input voltage	400 V 3 phases
Input voltage	380 V 415 V
Output voltage	400 V 3 phases
Output voltage	380 V 415 V
Rated power in W	10 KW
Rated power in VA	10 KVA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Battery type	Internal modular battery VRLA
Provided equipment	Battery modules ship installed Dust filter EcoStruxure IT ready (UPS) Installation guide Integrated network management Power modules ship installed Start-up service

General

Bypass voltage tolerance	+/- 10 %
Redundant	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical

Colour	White
Height	148.5 Cm
Width	52.1 Cm
Depth	84.7 Cm
Net weight	320 Kg
USB compatible	No

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 4-wire (3P + E) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	340...460 V 400 V
Maximum input current	18 A
Max short time withstand current	65 KA
Input harmonic distortion	Less than 3 % for full load
Load power factor	From 0.7 leading to 0.7 lagging without any derating
Cos phi	0.99

Output

Maximum configurable power in W	10 KW
Harmonic distortion	Less than 3 %
Output frequency	50 Hz sync to mains 60 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	2.5
Wave type	Sine wave
Output voltage tolerance	+/-1% after 50ms
Output harmonic distortion	< 1% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in static bypass
Maximum configurable power in VA	10 KVA

Conformance

Product certifications	UL 1778 5th edition
Standards	CSA C22.2 No 107.3 EN/IEC 62040-1 EN/IEC 62040-2 EN/IEC 62040-3 IEC 60721-4-2 level 2M2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3281 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0.00...3048.00 M
Acoustic level	55 dBA

Batteries & Runtime

Battery voltage	480 V
Discharge battery voltage	384 V DC
Max current discharge	27 A
Battery power in VAH	0 VAh runtime
Extended runtime	0

Communications & Management

Free slots	1
Control panel	Touch screen LCD user interface
Alarm	Audible and visible alarms prioritized by severity

Packing Units

Package 1 Weight	360 Kg
Package 1 Height	168 Cm
Package 1 width	64 Cm
Package 1 Length	99 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Product Life Status : Commercialised
