

Product data sheet

Characteristics

GVS BPSU20K60H

Maintenance Bypass Panel, single unit,
20-60kW 400V wallmount, for Galaxy VS and
Easy UPS 3S



Overview

Presentation	Maintenance bypass panel for complete isolation of the UPS during service operations.
Lead time	Usually Ships within 2 Weeks

Physical

Height	60 Cm
Width	55 Cm
Depth	22 Cm
Net weight	25 Kg

Environmental

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...55 °C

Packing Units

Package 1 Weight	40 Kg
Package 1 Height	120 Cm
Package 1 width	80 Cm
Package 1 Length	48 Cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Optimized Energy Efficiency

Energy efficient product

Take-back

Take-back program available

Product Life Status :

Commercialised