



Principal

Gama	TeSys
Device short name	GVAN
Tipo de producto o componente	Auxiliary contact block
Compatibilidad del producto	GV3P GV2LE GV2ME GV2RT GV3L GV2P GV2L
Mounting location	Left side
Pole contact composition	1 NO + 1 NC
Conexiones - terminales	Screw clamp terminals 1 cable 0.75...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.75...2.5 mm ² - cable stiffness: flexible - without cable end Screw clamp terminals 2 cable 0.75...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 0.75...1.5 mm ² - cable stiffness: flexible - with cable end Screw clamp terminals 1 cable 1...2.5 mm ² - cable stiffness: solid Screw clamp terminals 2 cable 1...2.5 mm ² - cable stiffness: solid

Complementos

[Ui] rated insulation voltage	600 V - conforming to UL 508 690 V - conforming to IEC 60947-1 600 V - conforming to CSA C22.2 No 14
[Ue] tensión de funcionamiento nominal	48...690 V AC 24...240 V CC
[Ith] conventional free air thermal current	6 A
Protection type	GB2CB... circuit breaker rating according to operational current for Ue ≤ 415 V GG fuse ≤ 10 A
Mechanical durability	100000 Ciclos
Minimum switching current	5 mA
Minimum switching voltage	17 V
Rated operational power in VA	300 VA at 48 V AC-15 - electrical durability: 100000 cycles 400 VA at 690 V AC-15 - electrical durability: 100000 cycles 500 VA at 110...127 V AC-15 - electrical durability: 100000 cycles 500 VA at 500 V AC-15 - electrical durability: 100000 cycles 650 VA at 440 V AC-15 - electrical durability: 100000 cycles 720 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 850 VA at 380...415 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	120 W at 240 V DC-13 - electrical durability: 100000 cycles 140 W at 110 V DC-13 - electrical durability: 100000 cycles 140 W at 24 V DC-13 - electrical durability: 100000 cycles 180 W at 60 V DC-13 - electrical durability: 100000 cycles 240 W at 48 V DC-13 - electrical durability: 100000 cycles
Tightening torque	≤ 1.4 N.m - on screw clamp terminals
Altura	89 mm
Anchura	9.3 mm
Profundidad	66 mm
Peso del producto	0.05 kg

Ambiente

Característica medioambiental	Normal environment
-------------------------------	--------------------

Garantía contractual

Warranty period	18 months
-----------------	-----------