

PRODUCT-DETAILS

316RS6

Surface socket-outlet, 6h, 16A, IP44, 3P+E



Información General

Extended Product Type	316RS6
Product ID	2CMA193106R1000
EAN	7392696931069
Catalog Description	Surface socket-outlet, 6h, 16A, IP44, 3P+E
Long Description	Wall mounted socket, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416449
E-Number (Finland)	2421203
E-Number (Norway)	1542313
EAN	7392696931069
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensiones

Product Net Width	79 mm
Product Net Height	79 mm

Product Net Length	132 mm
Product Net Depth / Length	132 mm
Product Net Weight	0.24 kg
Mechanical Drawings	9AKK107680A0701

Información de Embalaje

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696661065
Package Level 1 Units	box 10 piece
Package Level 2 Units	450 piece

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	18 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry.
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RS6
Mounting Holes	91x67
Mounting Type	Angled
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERS

Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700002D0001
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	0.8 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

