

PRODUCT-DETAILS

432RAU6

Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, angled, 3P+N+E



Información General

Extended Product Type	432RAU6
Product ID	2CMA193283R1000
EAN	7392696932837
Catalog Description	Socket-outlet, panel mounting, 6h, 32A, IP44, unified flange, angled, 3P+N+E
Long Description	Panel mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, unified flange, angled, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416670
E-Number (Finland)	2421276
E-Number (Norway)	1547453
EAN	7392696932837
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensiones

Product Net Width	110 mm
Product Net Height	110 mm

Product Net Length	117 mm
Product Net Depth / Length	117 mm
Product Net Weight	0.28 kg

Información de Embalaje

Package Level 1 Width	188 mm
Package Level 1 Depth / Length	175 mm
Package Level 1 Height	428 mm
Package Level 1 Gross Weight	2.8 kg
Package Level 1 EAN	7392696662833
Package Level 1 Units	box 10 piece
Package Level 2 Units	240 piece

Technical UL/CSA

Ampere Rating UL/CSA	32 A
Tightening Torque UL/CSA	10.6 in·lb

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CMC700005D0001
Declaration	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P_S#432RAU6
Mounting Holes	85x85
Mounting Type	Unified angled flange

Number of Poles	5
Order Multiple	10 piece
Product Main Type	ERAU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Recommended Screw Driver	PH2
RoHS Date	L23
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC00058M0001
Installation Manual	2CMC00058M0001
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

