



first lateral auxiliary switch 1 NO, 1 NC, screw terminal, for contactors 3RT1

| General technical data                                            |                                                 |
|-------------------------------------------------------------------|-------------------------------------------------|
| product brand name                                                | SIRIUS                                          |
| suitability for use                                               | Contactor relay and power contactor             |
| protection class IP on the front                                  | IP20                                            |
| ambient temperature                                               |                                                 |
| • during storage                                                  | -55 ... +80 °C                                  |
| • during operation                                                | -25 ... +60 °C                                  |
| mechanical service life (operating cycles) typical                | 10 000 000                                      |
| electrical endurance (operating cycles) at AC-15 at 230 V typical | 200 000                                         |
| contact reliability of auxiliary contacts                         | 1 faulty switching per 100 million (17 V, 1 mA) |
| insulation voltage with degree of pollution 3 at AC rated value   | 500 V                                           |
| surge voltage resistance rated value                              | 6 kV                                            |
| Auxiliary circuit                                                 |                                                 |
| number of NC contacts for auxiliary contacts                      |                                                 |
| • instantaneous contact                                           | 1                                               |
| number of NO contacts for auxiliary contacts                      |                                                 |
| • instantaneous contact                                           | 1                                               |
| operational current of auxiliary contacts at AC-12                |                                                 |
| • at 24 V                                                         | 10 A                                            |
| • at 230 V                                                        | 10 A                                            |
| • maximum                                                         | 10 A                                            |
| operational current                                               |                                                 |
| • of auxiliary contacts                                           |                                                 |
| — at AC-14                                                        |                                                 |
| — at 125 V                                                        | 6 A                                             |
| — at 250 V                                                        | 6 A                                             |
| — at AC-15                                                        |                                                 |
| — at 24 V                                                         | 6 A                                             |
| — at 230 V                                                        | 6 A                                             |
| — at 400 V                                                        | 3 A                                             |
| operational current                                               |                                                 |
| • of auxiliary contacts at DC-12                                  |                                                 |
| — at 24 V                                                         | 10 A                                            |
| — at 110 V                                                        | 3 A                                             |
| — at 220 V                                                        | 1 A                                             |
| • with 2 current paths in series at DC-12                         |                                                 |
| — at 24 V rated value                                             | 10 A                                            |
| — at 60 V rated value                                             | 10 A                                            |
| — at 110 V rated value                                            | 4 A                                             |
| — at 220 V rated value                                            | 2 A                                             |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 440 V rated value</li> <li>• with 3 current paths in series at DC-12 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                                                                                                                                                              | 1.3 A<br><br>10 A<br>10 A<br>10 A<br>3.6 A<br>2.5 A                                                                      |
| <b>operational current</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                          |
| <ul style="list-style-type: none"> <li>• of auxiliary contacts at DC-13 <ul style="list-style-type: none"> <li>— at 24 V</li> <li>— at 60 V</li> <li>— at 110 V</li> <li>— at 220 V</li> </ul> </li> <li>• with 2 current paths in series at DC-13 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> <li>• with 3 current paths in series at DC-13 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 60 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> </ul> </li> </ul> | 6 A<br>2 A<br>1 A<br>0.3 A<br><br>10 A<br>3.5 A<br>1.3 A<br>0.9 A<br>0.2 A<br><br>10 A<br>4.7 A<br>3 A<br>1.2 A<br>0.5 A |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                          |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | snap-on mounting                                                                                                         |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 10 mm                                                                                                                    |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 80 mm                                                                                                                    |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 71 mm                                                                                                                    |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                          |
| <b>type of electrical connection for auxiliary and control circuit</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | screw-type terminals                                                                                                     |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                                                          |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts <ul style="list-style-type: none"> <li>— finely stranded</li> <li>— with core end processing</li> </ul> </li> <li>• at AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 16), 2x (18 ... 14)                  |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                          |
| <b>product function mirror contact according to IEC 60947-4-1</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Yes                                                                                                                      |
| <ul style="list-style-type: none"> <li>• note</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | with 3RT1                                                                                                                |
| <b>product function positively driven operation according to IEC 60947-5-1</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | No                                                                                                                       |
| <b>Certificates/ approvals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                          |
| <b>General Product Approval</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <b>Functional Safety/Safety of Machinery</b>                                                                             |



[Confirmation](#)



[KC](#)



[Type Examination Certificate](#)

Declaration of Conformity

Test Certificates

Marine / Shipping



[Special Test Certificate](#)



[Confirmation](#)[Special Test Certificate](#)[Vibration and Shock](#)

## Further information

## Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

## Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

## Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RH1921-1DA11>


## Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RH1921-1DA11>


## Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RH1921-1DA11>


## Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RH1921-1DA11&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RH1921-1DA11&lang=en)

## Links / left



## Rechts / right



last modified:

1/7/2021 