

PRODUCT-DETAILS

HKF1-11

HKF1-11 Auxiliary Contact



Información General

Extended Product Type	HKF1-11
Product ID	1SAM201901R1001
EAN	4013614320354
Catalog Description	HKF1-11 Auxiliary Contact
Long Description	HKF1-11 Aux.-contact for front mounting

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Descargas Populares

Data Sheet, Technical Information	1SBC100192C02--
Instructions and Manuals	2CDC131011M6802 2CDC131034M6801 2CDC131022M6802

Dimensiones

Product Net Width	45 mm
Product Net Height	12.5 mm

Product Net Depth / Length	26.5 mm
Product Net Weight	0.015 kg

Technical

Terminal Type	Screw Terminals
Rated Operational Voltage	250 V
Rated Operational Current AC-15 (I _e)	(120 V) 3 A (240 V) 1.5 A (24 V) 3 A
Rated Operational Current DC-13 (I _e)	(125 V) 0.27 A (24 V) 1 A (250 V) 0.11 A
Rated Frequency (f)	Auxiliary Circuit DC Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz
Rated Impulse Withstand Voltage (U _{imp})	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U _i)	250 V
Degree of Protection	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 1.0 ... 2.5 mm ²
Tightening Torque	Auxiliary Circuit 0.8 ... 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 8 mm
Recommended Screw Driver	M3 Pozidriv 2
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-5-1 UL 508 UL 60947-1 UL 60947-5-1
Product Name	Auxiliary Contact
Suitable For	MS116 MS132 MO132 MS165 MO165
Suitable for Product Class	Manual Motor Starter
Accessory Group	Electrical
Accessory Type	Auxiliary Contact

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 250 V AC
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 7 in·lb
Contact Rating UL/CSA	B300 R300

Ambiente

Ambient Air Temperature	Funcionamiento -25 ... +60 °C Almacenamiento -50 ... +80 °C
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificados y Declaraciones (Número de Documento)

ABS Certificate	1SAA963001-0101
BV Certificate	1SAA963002-0201
CB Certificate	1SAA963003-2001
CCC Certificate	1SAA918002-3802
cUL Certificate	cUL_E137861
Declaration of Conformity - CE	1SAD938504-0196
	1SAD938507-0190
	1SAD938504-0198
	1SAD938505-0197
	1SAD938506-0191
	1SAD938507-0188
	1SAD938508-0183
	1SAD938514-0125
	1SAD938521-0060
	1SAD938503-0304
DNV GL Certificate	1SAA963001-0304
EAC Certificate	1SAA963000-2701
GOST Certificate	1SAA937000-2703
Instructions and Manuals	2CDC131011M6802
	2CDC131034M6801
	2CDC131022M6802
LR Certificate	1SAA963001-0501
	1SAA963001-0502
	1SAA963000-0505
RINA Certificate	Rina_MS132
RoHS Information	1SAA963001-4407
UL Certificate	UL_E137861

Información de Embalaje

Package Level 1 Width	148 mm
Package Level 1 Depth / Length	36 mm
Package Level 1 Height	50 mm
Package Level 1 Gross Weight	0.195 kg
Package Level 1 EAN	4013614481413
Package Level 1 Units	box 10 piece
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	10.125 kg
Package Level 2 EAN	4013614522727
Package Level 2 Units	500 piece

Clasificaciones		
Object Classification Code		Q
ETIM 4	EC002498 - Accessories for low-voltage switch technology	
ETIM 5	EC000041 - Auxiliary contact block	
ETIM 6	EC000041 - Auxiliary contact block	
ETIM 7	EC000041 - Auxiliary contact block	
eClass		7.0 27371302
UNSPSC		39121522
IDEA Granular Category Code (IGCC)	4742 >> Electrical contacts	
E-Number (Sweden)		3112001

Where Used (as a spare part for "Products")				
Identifier		Description	Quantity	Unit Of Measure
ACS 2000		No Description Available	1	piece
ACS 1000		No Description Available	1	piece
ACS 5000 Water Cooled		No Description Available	1	piece
ACS 6000		No Description Available	1	piece

Product specific part data		
Product	Category	Drive Part Category
ACS 2000	ACS2000	Switches, Relays, Contactors
ACS 1000	ACS1000	Switches, Relays, Contactors
ACS 5000 Water Cooled	ACS5000	Switches, Relays, Contactors
ACS 6000	ACS6000	Switches, Relays, Contactors

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Guardamotores → Manual Motor Starters Accessories

Convertidores de frecuencia → Convertidores de frecuencia de media tensión → Convertidores de frecuencia de propósito general → ACS5000

Convertidores de frecuencia → Convertidores de frecuencia de media tensión → Industrial drives → ACS1000

Convertidores de frecuencia → Convertidores de frecuencia de media tensión → Industrial drives → ACS2000

Convertidores de frecuencia → Convertidores de frecuencia de media tensión → Industrial drives → ACS6000

