

COM connecting cable 0.3 m for 3RW50



Figure similar

|                               |                      |
|-------------------------------|----------------------|
| product brand name            | SIRIUS               |
| product category              | Connecting cables    |
| product designation           | COM connecting cable |
| design of the product         | 0.3 m, round         |
| manufacturer's article number | 3RW50                |
| • of soft starter             |                      |
| Substance Prohibitance (Date) | 09/23/2019           |

| Ambient conditions                               |                |
|--------------------------------------------------|----------------|
| ambient temperature during storage and transport | -40 ... +80 °C |

| Safety related data                                     |                                                  |
|---------------------------------------------------------|--------------------------------------------------|
| protection class IP on the front according to IEC 60529 | IP20                                             |
| touch protection on the front according to IEC 60529    | finger-safe, for vertical contact from the front |

| Certificates/ approvals  |                                 |                           |
|--------------------------|---------------------------------|---------------------------|
| General Product Approval | For use in hazard-ous locations | Declaration of Conformity |



[Confirmation](#)



[Explosion Protection Certificate](#)



| Declaration of Conformity | Test Certificates | Marine / Shipping |
|---------------------------|-------------------|-------------------|
|---------------------------|-------------------|-------------------|



EG-Konf.

[Type Test Certificates/Test Report](#)



ABS



LRS



PRS



DNV GL

| other |
|-------|
|-------|

[Confirmation](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RW5900-0CC00>

### Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RW5900-0CC00>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5900-0CC00>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RW5900-0CC00&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RW5900-0CC00&lang=en)

### Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RW5900-0CC00/char>

### Characteristic: Installation altitude

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RW5900-0CC00&objecttype=14&gridview=view1>

### Simulation Tool for Soft Starters (STS)

<https://support.industry.siemens.com/cs/ww/en/view/101494917>

last modified:

12/15/2020 

