

# Product data sheet

Specifications



## Photoelectric sensors XU, XUB, receiver, Sn 15 m, 12...24 VDC, M12

XUB2APBNM12R

### Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor receiver
Sensor name	XUB
Sensor design	Cylindrical M18
Detection system	Thru beam
Material	Plastic
Line of sight type	Axial
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NC
Electrical connection	1 male connector M12, 4 pins
Product specific application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	15 m thru beam need a transmitter XUB2AKSNM12T

### Complementary

Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	20 m thru beam
Output type	Solid state
Add on output	Without
Status LED	1 LED (yellow) for output state
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...36 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 500 Hz

<b>Maximum voltage drop</b>	<1.5 V (closed state)
<b>Current consumption</b>	35 mA no-load
<b>Maximum delay first up</b>	15 ms
<b>Maximum delay response</b>	1 ms
<b>Maximum delay recovery</b>	1 ms
<b>Setting-up</b>	Without sensitivity adjustment
<b>Diameter</b>	18 mm
<b>Length</b>	60 mm
<b>Net weight</b>	0.04 kg

## Environment

<b>Product certifications</b>	CSA UL CE
<b>Ambient air temperature for operation</b>	-25...55 °C
<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Vibration resistance</b>	7 gn, amplitude = +/- 1.5 mm (f = 10...55 Hz) conforming to IEC 60068-2-6
<b>Shock resistance</b>	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
<b>IP degree of protection</b>	IP65 double insulation conforming to IEC 60529 IP67 double insulation conforming to IEC 60529 IP69K double insulation conforming to DIN 40050

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Weight</b>	31.0 g
<b>Package 1 Height</b>	4.2 cm
<b>Package 1 width</b>	6.7 cm
<b>Package 1 Length</b>	9.6 cm
<b>Unit Type of Package 2</b>	S01
<b>Number of Units in Package 2</b>	22
<b>Package 2 Weight</b>	1.007 kg
<b>Package 2 Height</b>	15.0 cm
<b>Package 2 width</b>	15.0 cm
<b>Package 2 Length</b>	40.0 cm

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
<b>Mercury free</b>	Yes
<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>

**California proposition 65**


WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Contractual warranty****Warranty**

18 months


Dimensions

---




### Wiring Schemes

#### M12 Connector



1 : (+)  
3 : (-)  
4 : OUT/Output

#### PNP Outputs



### Detection Curves

---

