

## PRODUCT-DETAILS

# CR-P024DC2

CR-P024DC2 Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/8A



## Información General

|                       |                                                                                                                                                                                                                                                                                                                             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CR-P024DC2                                                                                                                                                                                                                                                                                                                  |
| Product ID            | 1SVR405601R1000                                                                                                                                                                                                                                                                                                             |
| EAN                   | 4013614498237                                                                                                                                                                                                                                                                                                               |
| Catalog Description   | CR-P024DC2 Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/8A                                                                                                                                                                                                                                                             |
| Long Description      | The CR-P024DC2 pluggable interface relay is from the CR-P (pcb) relay range. This relay operates with a 24 V DC rated control supply voltage and has a 2 c/o (SPDT) output with contacts rated at 250 V / 8 A. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories. |

## Clasificación

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 10 piece |
| Customs Tariff Number  | 85364900 |

## Descargas Populares

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC117001D0203 |
| Instructions and Manuals          | 1SVC405600M9000 |

## Dimensiones

|                   |         |
|-------------------|---------|
| Product Net Width | 12.7 mm |
|-------------------|---------|

|                            |          |
|----------------------------|----------|
| Product Net Height         | 15.7 mm  |
| Product Net Depth / Length | 29 mm    |
| Product Net Weight         | 0.014 kg |

## Technical

|                                                |                                    |
|------------------------------------------------|------------------------------------|
| Function                                       | Pluggable pcb interface relay CR-P |
| Sub-Function                                   | Relay w/o built in LED             |
| Output                                         | 2 c/o (SPDT) contacts              |
| Output Signal                                  | 250 V / 8 A                        |
| Rated Control Supply Voltage (U <sub>s</sub> ) | 24 V DC                            |

## Ambiente

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificados y Declaraciones (Número de Documento)

|                                |                             |
|--------------------------------|-----------------------------|
| CCC Certificate                | CCC_2007010303228779        |
| CSA Certificate                | CSA_1587291                 |
| cUR Certificate                | cUR_E244330                 |
| Declaration of Conformity - CE | No declaration needed       |
| EAC Certificate                | EAC_RU_C-DE.ME77.B.00446-19 |
| Environmental Information      | 1SAA981009-2401             |
| Instructions and Manuals       | 1SVC405600M9000             |
| RMRS Certificate               | RMRS_1740019250             |
| RoHS Information               | 1SVD981001-4400             |
| UR Certificate                 | UR_E244330                  |
| VDE Certificate                | VDE_40019129                |

## Información de Embalaje

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 10 piece      |
| Package Level 1 Width          | 332 mm        |
| Package Level 1 Height         | 28 mm         |
| Package Level 1 Depth / Length | 17 mm         |
| Package Level 1 Gross Weight   | 0.157 kg      |
| Package Level 1 EAN            | 4013614373008 |

## Clasificaciones

|                            |                            |
|----------------------------|----------------------------|
| Object Classification Code | K                          |
| ETIM 4                     | EC001437 - Switching relay |
| ETIM 5                     | EC001437 - Switching relay |
| ETIM 6                     | EC001437 - Switching relay |
| ETIM 7                     | EC001437 - Switching relay |
| eClass                     | 7.0 27371601               |
| E-Number (Sweden)          | 4005308                    |

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos de control → Relés electrónicos → Relés de interface

